

**Comment of the Comment of the Comm

UNICOAT COLOR

UNICOAT COLOR

TECHNICAL DATA

Density (g/cm3): 1,02 - 1,5 kg/l

Solids content in volume: 40%

SAFETY DATA

VOC level: 35 g/l 35 g/l VOC readymix: VOC category: A/j VOC limit: 140 g/l

SHELF LIFE

Can be kept for a minimum of 12 months when stored in a dry, cool, and frost-free environment in the original unopened packaging.

Date issued: 05/02/2025

Available colours & pack sizes: Please refer to the respective product page on www.rust-oleum.eu for an overview of actual available colours and pack sizes.

Disclaimer: The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. The user will be deemed to have satisfied him/herself independently as to the suitability of our products for his/her own particular purpose. In no event shall Rust-Oleum Europe be liable for consequential or incidental damages. Products must be stored, handled, and applied under conditions complying with Rust-Oleum Europe recommendations detailed within the latest copy of the product data sheet. It is the users responsibility to ensure that they have the current copy. Latest copies of the product data sheet is available for free and downloadable from www.rust-oleum.eu or upon a request to our Customer Services department. Rust-Oleum Europe reserves the right to change the properties of its' products without prior notification.

Rust-Oleum Netherlands B.V. Zilverenberg 16 5234 GM 's-Hertogenbosch The Netherlands T: +31 (0) 165 593 636 F: +31 (0) 165 593 600

Tor Coatings Ltd (Rust-Oleum Ind Shadon Way, Portobello Ind. Estate Birtley, Chester-le-Street DH3 2RE United Kingdom T: +44 (0)1914 113 146 F: +44 (0)1914 113 147

Rust-Oleum France S.A.S. 38, av. du Gros Chêne 95322 Herblay France

T: +33(0) 130 40 00 44 F: +33(0) 130 40 99 80 info@rust-oleum.eu

N.V. Martin Mathys S.A. Kolenbergstraat 23 3545 Zelem

Belgium T:+32 (0) 13 460 200 F:+32 (0) 13 460 201 info@rust-oleum.eu