

PROCHEMKO



UNI-WASH HD

Economical concentrated cleaner with hardness stabilisers

- Removes grease, road grime, and atmospheric deposits
- No risk of limescale crust in machines
- Usable in hard water
- For use on plastics, metals, coatings, concrete, and tiles
- Economical concentrated formula

UNI-WASH HD

DESCRIPTION

A highly-concentrated cleaner based on anionic and non-ionic surfactants and hardness stabilisers for use on plastics, metals, cured lacquers, floors, such as concrete and tiles.

RECOMMENDED USE

Uni-Wash H.D. is used to remove street grime, atmospheric deposits from vehicles, and dirty and/or greasy floors.

By adding hardness stabilisers, the product can be used in extremely hard water in high-pressure equipment, and other cleaning equipment, without the risk of limescale crust in the spray heads or dosing systems.

Also suitable for use on plastics, rubber, cured varnishes, floors with a variety of structures, and most metals.

PRACTICAL CONSUMPTION

Consumption is heavily dependent on the degree of dilution, the surface, and the degree of fouling.

DIRECTIONS FOR USE

Uni-Wash H.D. is used in floor cleaning machines, spray equipment, high-pressure cleaners, and also by hand.

Floor cleaning : ratio of 1 to 50/100 depending on the type of dirt the dosing tank.

Spray equipment : 5% solution in water, spray the object and then, after a few minutes, spray off with a powerful water jet.

High-pressure equipment: 10% solution in the dosing tank.

Adjust the dose so that you spray with a 0.5% solution.

Rinse with water.

With stubborn dirt, we recommend that you allow the product to soak in longer.

APPLICATION CONDITIONS

Can be used in all circumstances, but do not use in full sunlight or in frosty conditions.

CLEANING OF EQUIPMENT / SPILLS

Rinse with water immediately after use.

REMARKS

Dispose of remaining product, empty packaging, and waste water as chemical waste in accordance with the local regulations and legal requirements.

PH

9,50

SHELF LIFE

Can be kept for a minimum of 12 months when stored in a dry, cool and frost-free environment in the original unopened packaging.

Date issued: 05/02/2025

Available colours & pack sizes: Please refer to the respective product page on www.rust-oleum.eu for an overview of actual available colours and pack sizes.

Disclaimer: The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. The user will be deemed to have satisfied him/herself independently as to the suitability of our products for his/her own particular purpose. In no event shall Rust-Oleum Europe be liable for consequential or incidental damages. Products must be stored, handled, and applied under conditions complying with Rust-Oleum Europe recommendations detailed within the latest copy of the product data sheet. It is the users responsibility to ensure that they have the current copy. Latest copies of the product data sheet is available for free and downloadable from www.rust-oleum.eu or upon a request to our Customer Services department. Rust-Oleum Europe reserves the right to change the properties of its' products without prior notification.

Rust-Oleum Netherlands B.V.
Zilverenberg 16
5234 GM 's-Hertogenbosch
The Netherlands
T : +31 (0) 165 593 636
F : +31 (0) 165 593 600
info@rust-oleum.eu

Tor Coatings Ltd (Rust-Oleum Industrial)
Shadon Way, Portobello Ind. Estate
Birtley, Chester-le-Street
DH3 2RE United Kingdom
T : +44 (0)1914 113 146
F : +44 (0)1914 113 147
info@rust-oleum.eu

Rust-Oleum France S.A.S.
38, av. du Gros Chêne
95322 Herblay
France
T : +33(0) 130 40 00 44
F : +33(0) 130 40 99 80
info@rust-oleum.eu

N.V. Martin Mathys S.A.
Kolenbergstraat 23
3545 Zelem
Belgium
T : +32 (0) 13 460 200
F : +32 (0) 13 460 201
info@rust-oleum.eu