



VANEX

Strong degreaser for coated surfaces and glass

- · Removes caked on dirt such as insects, tar and oil
- No effect on unsaponifiable paintwork
- · Leaves no traces or stripes
- · Also ideal for cleaning vehicles and greenhouses
- Concentrated formula, for max. dilution 1:30



DESCRIPTION

A strong all-purpose alkaline cleaner based on surfactants, cleaning enhancers and lye for plastisol panels, lorries, buses, machines, greenhouses and more.

RECOMMENDED USE

Suitable for cleaning plastisol sheeting, lorries, buses, tanks, delivery vans, bulk transport carriers, road construction machines as well as cleaning greenhouses in horticulture, etc.

THEORETICAL CONSUMPTION

Approx 20 m²/l

PRACTICAL CONSUMPTION

Consumption depends heavily on the level of dirt, dilution and type of surface.

DIRECTIONS FOR USE

- Dilute Vanex with water to a maximum of 1: 20, depending on the amount of dirt
- Apply the product using a brush or low pressure nozzle
- Allow the product to work for a few minutes
- Rinse off with clean water

APPLICATION CONDITIONS

Minimum ambient temperature: 5°C Maximum relative humidity: 100% Minimum surface temperature: 5°C Maximum surface temperature: 30°C

CLEANING OF EQUIPMENT / SPILLS

Rinse with clean water directly after use.

REMARKS

Dispose of remaining product and empty packaging as chemical waste, in accordance with the local regulations and legal requirements.

PH

13,20

SHELF LIFE

Minimum of 12 months when stored in a dry, cool and frost-free environment in the original, unopened packaging.

Date issued: 05/02/2025

Available colours & pack sizes: Please refer to the respective product page on www.rust-oleum.eu for an overview of actual available colours and pack sizes.

Disclaimer: The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. The user will be deemed to have satisfied him/herself independently as to the suitability of our products for his/her own particular purpose. In no event shall Rust-Oleum Europe be liable for consequential or incidental damages. Products must be stored, handled, and applied under conditions complying with Rust-Oleum Europe recommendations detailed within the latest copy of the product data sheet. It is the users responsibility to ensure that they have the current copy. Latest copies of the product data sheet is available for free and downloadable from www.rust-oleum.eu or upon a request to our Customer Services department. Rust-Oleum Europe reserves the right to change the properties of its' products without prior notification.

Rust-Oleum Netherlands B.V. Zilverenberg 16 5234 GM 's-Hertogenbosch The Netherlands T:+31 (0) 165 593 636 F:+31 (0) 165 593 600 Tor Coatings Ltd (Rust-Oleum Industrial)
Shadon Way, Portobello Ind. Estate
Birtley, Chester-le-Street
DH3 2RE United Kingdom
T: +44 (0)1914 113 146
F: +44 (0)1914 113 147
into@rust-oleum.eu

Rust-Oleum France S.A.S. 38, av. du Gros Chêne 95322 Herblay France T: +33(0) 130 40 00 44 F: +33(0) 130 40 99 80 info@ust-oleum.eu N.V. Martin Mathys S.A.
Kolenbergstraat 23
3545 Zelem
Belgium
T: +32 (0) 13 460 200
F: +32 (0) 13 460 201
info@rust-oleum.eu