



X1 ANTI-SPATTER WELD SPRAY

Prevents adhesion of weld spatter

- Non corrosive
- Non silicon
- Temperature range: -5 °C to 200 °C
- Contains no chlorinated solvents

KNOW-HOW TO PROTECT[™]

WWW.RUST-OLEUM.EU

X1 ANTI-SPATTER WELD SPRAY

DESCRIPTION

High quality technical spray that effectively prevents the adhesion of weld spatter to metal surfaces. It protects welded materials from corrosion. X1 eXcellent Multi-Purpose Weld spray provides eXcellent performance. It withstands extreme temperatures, will resist chemical attacks and has excellent thermal conductivity.

RECOMMENDED USE

Work pieces, welding equipment. Suitable for MIG. ARC or TIG welding.

APPLICATION & THINNING: AEROSOL

Shake aerosol before use. Spray a light film onto surface from 20 to 30 cm. Do not over apply.

SHELF LIFE

Minimum of 3 years from date of production in unopened cans, if stored in dry, well ventilated areas, not in direct sunlight at temperatures between 5° and 35°C.

Date issued: 20/03/2025

Available colours & pack sizes: Please refer to the respective product page on www.rust-oleum.eu for an overview of actual available colours and pack sizes.

Disclaimer: The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. The user will be deemed to have satisfied him/herself independently as to the suitability of our products for his/her own particular purpose. In no event shall Rust-Oleum Europe be liable for consequential or incidental damages. Products must be stored, handled, and applied under conditions complying with Rust-Oleum Europe recommendations detailed within the latest copy of the product data sheet. It is the users responsibility to ensure that they have the current copy. Latest copies of the product data sheet is available for free and downloadable from www.rust-oleum.eu or upon a request to our Customer Services department. Rust-Oleum Europe reserves the right to change the properties of its' products without prior notification.

Rust-Oleum Netherlands B.V.

Rust-Oleum Netherlands E Zilverenberg 16 5234 GM 's-Hertogenbosch The Netherlands T : +31 (0) 165 593 636 F : +31 (0) 165 593 600 info@rust-oleum.eu

ns I tri (Rust-Ol Tor Coatin strial) Shadon Way, Portobello Ind. Estate Birtley, Chester-le-Street DH3 2RE United Kingdom T : +44 (0)1914 113 146 F : +44 (0)1914 113 147 info@rust-oleum eu

Rust-Oleum France S.A.S. 38, av. du Gros Chêne 95322 Herblay France T : +33(0) 130 40 00 44 F : +33(0) 130 40 99 80 info@rust-oleum.eu

N.V. Martin Mathys S.A Kolenbergstraat 23 3545 Zelem Belgium T : +32 (0) 13 460 200 F : +32 (0) 13 460 201 info@rust-oleum.eu



WWW.RUST-OLEUM.EU