

**RUST-OLEUM®**  
— INDUSTRIAL —



## **X1 MULTI-PURPOSE SPRAY**

# **Lubricates, cleans and protects**

- Stops squeaking
- Creeping properties
- Displaces water
- A film layer is left on the surface after cleaning
- Does not contain silicon

**KNOW-HOW TO PROTECT™**

**WWW.RUST-OLEUM.EU**

# X1 MULTI-PURPOSE SPRAY

## DESCRIPTION

General purpose lubrication fluid that protects and cleans metal and plastic parts. This excellent penetrating fluid has anti-corrosive and water repellent properties. It leaves a protective film layer after use. reinforced with BoroTecX™, an excellent penetrating fluid with anti-corrosive and water repellent and displacing properties. It leaves a protective film layer after use.

## RECOMMENDED USE

Lubricating cables, chains, locks, switches and contacts - protection of metal surfaces against rust - removes oil, grease, wax and leaves a protection film after cleaning - protection of electrical terminals from moisture and corrosion - displaces water in automotive ignition circuits and contacts - frees and loosens rusted parts - will help to remove adhesive labels – can be used as stainless steel cleaner.

## SURFACE PREPARATION

Ensure electrical equipment is isolated and check surfaces for compatibility prior to application. Clean and remove old lubricant from components prior to application.

## APPLICATION CONDITIONS

Apply at temperatures between 5° and 35°C.

## APPLICATION & THINNING: AEROSOL

Shake aerosol before use. Spray a light film onto surface from 20 to 30 cm. Do not over apply.

## SHELF LIFE

Minimum of 3 years from date of production in unopened cans, if stored in dry, well ventilated areas, not in direct sunlight at temperatures between 5° and 35°C

Date issued: 13/05/2025

**Available colours & pack sizes:** Please refer to the respective product page on [www.rust-oleum.eu](http://www.rust-oleum.eu) for an overview of actual available colours and pack sizes.

**Disclaimer:** The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. The user will be deemed to have satisfied him/herself independently as to the suitability of our products for his/her own particular purpose. In no event shall Rust-Oleum Europe be liable for consequential or incidental damages. Products must be stored, handled, and applied under conditions complying with Rust-Oleum Europe recommendations detailed within the latest copy of the product data sheet. It is the users responsibility to ensure that they have the current copy. Latest copies of the product data sheet is available for free and downloadable from [www.rust-oleum.eu](http://www.rust-oleum.eu) or upon a request to our Customer Services department. Rust-Oleum Europe reserves the right to change the properties of its' products without prior notification.

**Rust-Oleum Netherlands B.V.**  
Zilverenberg 16  
5234 GM 's-Hertogenbosch  
The Netherlands  
T : +31 (0) 165 593 636  
F : +31 (0) 165 593 600  
[info@rust-oleum.eu](mailto:info@rust-oleum.eu)

**Tor Coatings Ltd (Rust-Oleum Industrial)**  
Shadon Way, Portobello Ind. Estate  
Birtley, Chester-le-Street  
DH3 2RE United Kingdom  
T : +44 (0)1914 113 146  
F : +44 (0)1914 113 147  
[info@rust-oleum.eu](mailto:info@rust-oleum.eu)

**Rust-Oleum France S.A.S.**  
38, av. du Gros Chêne  
95322 Herblay  
France  
T : +33(0) 130 40 00 44  
F : +33(0) 130 40 99 80  
[info@rust-oleum.eu](mailto:info@rust-oleum.eu)

**N.V. Martin Mathys S.A.**  
Kolenbergstraat 23  
3545 Zelem  
Belgium  
T : +32 (0) 13 460 200  
F : +32 (0) 13 460 201  
[info@rust-oleum.eu](mailto:info@rust-oleum.eu)