

RUST-OLEUM®
— INDUSTRIAL —



X1 PTFE SPRAY

A high purity, light lubricant containing PTFE

- High anti-wear characteristics
- Contains PTFE
- Water repellent
- Ultra low friction coefficient
- Temperature range: -40 °C to 120 °C

KNOW-HOW TO PROTECT™

WWW.RUST-OLEUM.EU

X1 PTFE SPRAY

DESCRIPTION

High purity, light lubricant containing PTFE. Suitable for applications requiring a clean, light film. It has outstanding lubrication and water repellent properties. reinforced with BoroTec™. It has outstanding lubrication and water repellent properties.

RECOMMENDED USE

Light duty chains, hinges, slides and gears. Ideal for air tools and other small machinery. Clean product so suitable for use in car interiors and air tools. Will lubricate garden and horticultural equipment. Ideal for use on commercial sewing and knitwear machinery.

SURFACE PREPARATION

Ensure electrical equipment is isolated and check surfaces for compatibility prior to application. Clean and remove old lubricant from components prior to application.

APPLICATION CONDITIONS

Apply at temperatures between 5° and 35°C.

APPLICATION & THINNING: AEROSOL

Shake aerosol before use. Spray a light film onto surface from 20 to 30 cm. Do not over apply.

SHELF LIFE

Minimum of 3 years from date of production in unopened cans, if stored in dry, well ventilated areas, not in direct sunlight at temperatures between 5° and 35°C.

Date issued: 20/03/2025

Available colours & pack sizes: Please refer to the respective product page on www.rust-oleum.eu for an overview of actual available colours and pack sizes.

Disclaimer: The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. The user will be deemed to have satisfied him/herself independently as to the suitability of our products for his/her own particular purpose. In no event shall Rust-Oleum Europe be liable for consequential or incidental damages. Products must be stored, handled, and applied under conditions complying with Rust-Oleum Europe recommendations detailed within the latest copy of the product data sheet. It is the users responsibility to ensure that they have the current copy. Latest copies of the product data sheet is available for free and downloadable from www.rust-oleum.eu or upon a request to our Customer Services department. Rust-Oleum Europe reserves the right to change the properties of its' products without prior notification.

Rust-Oleum Netherlands B.V.

Zilverenberg 16
5234 GM 's-Hertogenbosch
The Netherlands
T: +31 (0) 165 593 636
F: +31 (0) 165 593 600
info@rust-oleum.eu

Tor Coatings Ltd (Rust-Oleum Industrial)

Shadon Way, Portobello Ind. Estate
Birtley, Chester-le-Street
DH3 2RE United Kingdom
T: +44 (0)1914 113 146
F: +44 (0)1914 113 147
info@rust-oleum.eu

Rust-Oleum France S.A.S.

38, av. du Gros Chêne
95322 Herblay
France
T: +33(0) 130 40 00 44
F: +33(0) 130 40 99 80
info@rust-oleum.eu

N.V. Martin Mathys S.A.

Kolenbergstraat 23
3545 Zelem
Belgium
T: +32 (0) 13 460 200
F: +32 (0) 13 460 201
info@rust-oleum.eu