

RUST-OLEUM®
— INDUSTRIAL —



1614 X1 FREEZE RELEASE SPRAY

High quality rust releaser with shock effect

- Water repellent
- Temperature range: -50 °C to 170 °C
- Shocks components with rapid temperature reduction

KNOW-HOW TO PROTECT™

WWW.RUST-OLEUM.EU

1614 X1 FREEZE RELEASE SPRAY

OPIS

High quality rust releaser to loosen rusted parts by shocking, with a rapid temperature decrease and then using an advanced chemical action to penetrate, lubricate and release the components. Reinforced with BoroTecX™. This gives the advantages of outstanding lubrication properties and it repels water.

ZALECANE UŻYCIE

Fasteners, connections fastened with screws. Releases rusted and seized screws, bolts, studs and other seized components.

PRZYGOTOWANIE POWIERZCHNI

Ensure electrical equipment is isolated and check surfaces for compatibility prior to application. Clean and remove old lubricant from components prior to application.

WARUNKI APLIKACJI

Apply at temperatures between 5° and 35°C.

APLIKACJA I ROZCIEŃCZANIE: AEROSOL

Shake aerosol before use. Spray a light film onto surface from 20 to 30 cm. Do not over apply.

OKRES TRWAŁOŚCI PRODUKTU

Minimum of 3 years from date of production in unopened cans, if stored in dry, well ventilated areas, not in direct sunlight at temperatures between 5° and 35°C.

Data wydania: 20/03/2025

Dostępne kolory i opakowania: Więcej informacji na temat dostępnych kolorów i opakowań na stronie internetowej www.rust-oleum.eu.

Zrzeczenie się: Informacje tu zawarte przekazywane są w dobrej wierze, bez udzielania gwarancji. Ponieważ warunki aplikacji są poza naszą kontrolą, Rust-Oleum nie może ponosić jakiegokolwiek odpowiedzialności lub obciążeń finansowych, które mogą wynikać z niewłaściwego zastosowania tego produktu. Produkt musi być przechowywany, transportowany i aplikowany zgodnie z zaleceniami Rust-Oleum. Użytkownik powinien zadbać o posiadanie najbardziej aktualnej karty produktu. Wszystkie karty dostępne są na stronie internetowej producenta lub dystrybutora. Firma zastrzega sobie prawo modyfikowania danych bez uprzedzenia.

Rust-Oleum Netherlands B.V.
Zilverenberg 16
5234 GM 's-Hertogenbosch
The Netherlands
T : +31 (0) 165 593 636
F : +31 (0) 165 593 600
info@rust-oleum.eu

Tor Coatings Ltd (Rust-Oleum Industrial)
Shadon Way, Portobello Ind. Estate
Birtley, Chester-le-Street
DH3 2RE United Kingdom
T : +44 (0)1914 113 146
F : +44 (0)1914 113 147
info@rust-oleum.eu

Rust-Oleum France S.A.S.
38, av. du Gros Chêne
95322 Herblay
France
T : +33(0) 130 40 00 44
F : +33(0) 130 40 99 80
info@rust-oleum.eu

N.V. Martin Mathys S.A.
Kolenbergstraat 23
3545 Zelem
Belgium
T : +32 (0) 13 460 200
F : +32 (0) 13 460 201
info@rust-oleum.eu