

RUST-OLEUM®
— INDUSTRIAL —



X1 SILICON SPRAY

Odourless and colourless dry lubricant

- Dry lubricant
- Stops squeaking
- Water resistant and repellent
- Temperature range: -40 °C to 200 °C

KNOW-HOW TO PROTECT™

WWW.RUST-OLEUM.EU

X1 SILICON SPRAY

ОПИСАНИЕ

High quality odourless and colourless superfine dry lubricant which possesses excellent thermal stability, for all types of general purpose lubrication applications. Reinforced with BoroTecX™, an ultra thin film lubricant with excellent lasting penetrating properties.

ПРЕПОРЪЧИТЕЛНА УПОТРЕБА

Lubricating cables, chains, bearings, pins, links, conveyors and hinges. Non stick for slides, shutters, drawers, zippers. Protection of metal surfaces against rust. Lubricating locks, hinges and other moving parts. Cleaning vinyl, plastic and rubber surfaces. Release agent for moulds and castings. Protects locks from freezing. Ideal for use in the pharmaceutical and other clean industries.

ПОДГОТОВКА НА ПОВЪРХНОСТТА

Ensure electrical equipment is isolated and check surfaces for compatibility prior to application. Clean and remove old lubricant from components prior to application.

УСЛОВИЯ ЗА НАНАСЯНЕ

Apply at temperatures between 5° and 35°C.

GROUP APPL THINNING 60 AEROSOL

Shake aerosol before use. Spray a light film onto surface from 20 to 30 cm. Do not over apply.

СРОК НА ГОДНОСТ

Minimum of 3 years from date of production in unopened cans, if stored in dry, well ventilated areas, not in direct sunlight at temperatures between 5° and 35°C.

Дата на издаване: 23/10/2025

Налични цветове и размери на опаковките: Моля, вижте съответната продуктова страница на www.rust-oleum.eu, за да се запознаете с актуалните налични цветове и размери на опаковките.

Отказ от отговорност: Информацията, съдържаща се в този документ, доколкото ни е известно, е вярна и точна и се предоставя добросъвестно, но без гаранция. Счита се, че потребителят се е уверил самостоятелно в пригодността на нашите продукти за неговата/нейната конкретна цел. При никакви обстоятелства Rust-Oleum Europe не носи отговорност за последващи или случайни щети. Продуктите трябва да се съхраняват, обработват и нанасят при условия, съответстващи на препоръките на Rust-Oleum Europe, подробно описани в последното копие на информационния лист на продукта. Отговорност на потребителите е да се уверят, че разполагат с актуалното копие. Последните копия на информационния лист за продукта са на разположение безплатно и могат да бъдат изтеглени от www.rust-oleum.eu или при запитване до нашия отдел за обслужване на клиенти. Rust-Oleum Europe си запазва правото да променя свойствата на своите продукти без предварително уведомление.

Rust-Oleum Netherlands B.V.
Zilverenberg 16
5234 GM 's-Hertogenbosch
The Netherlands
T: +31 (0) 165 593 636
F: +31 (0) 165 593 600
info@rust-oleum.eu

Tor Coatings Ltd (Rust-Oleum Industrial)
Shadon Way, Portobello Ind. Estate
Birtley, Chester-le-Street
DH3 2RE United Kingdom
T: +44 (0)1914 113 146
F: +44 (0)1914 113 147
info@rust-oleum.eu

Rust-Oleum France S.A.S.
38, av. du Gros Chêne
95322 Herblay
France
T: +33(0) 130 40 00 44
F: +33(0) 130 40 99 80
info@rust-oleum.eu

N.V. Martin Mathys S.A.
Kolenbergstraat 23
3545 Zelem
Belgium
T: +32 (0) 13 460 200
F: +32 (0) 13 460 201
info@rust-oleum.eu