

RUST-OLEUM®
— INDUSTRIAL —



X1 SILICON SPRAY

Odourless and colourless dry lubricant

- Dry lubricant
- Stops squeaking
- Water resistant and repellent
- Temperature range: -40 °C to 200 °C

KNOW-HOW TO PROTECT™

WWW.RUST-OLEUM.EU

X1 SILICON SPRAY

DESCRIPTION

High quality odourless and colourless superfine dry lubricant which possesses excellent thermal stability, for all types of general purpose lubrication applications. Reinforced with BoroTecX™, an ultra thin film lubricant with excellent lasting penetrating properties.

RECOMMENDED USE

Lubricating cables, chains, bearings, pins, links, conveyors and hinges. Non stick for slides, shutters, drawers, zippers. Protection of metal surfaces against rust. Lubricating locks, hinges and other moving parts. Cleaning vinyl, plastic and rubber surfaces. Release agent for moulds and castings. Protects locks from freezing. Ideal for use in the pharmaceutical and other clean industries.

SURFACE PREPARATION

Ensure electrical equipment is isolated and check surfaces for compatibility prior to application. Clean and remove old lubricant from components prior to application.

APPLICATION CONDITIONS

Apply at temperatures between 5° and 35°C.

APPLICATION & THINNING: AEROSOL

Shake aerosol before use. Spray a light film onto surface from 20 to 30 cm. Do not over apply.

SHELF LIFE

Minimum of 3 years from date of production in unopened cans, if stored in dry, well ventilated areas, not in direct sunlight at temperatures between 5° and 35°C.

Date issued: 20/03/2025

Available colours & pack sizes: Please refer to the respective product page on www.rust-oleum.eu for an overview of actual available colours and pack sizes.

Disclaimer: The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. The user will be deemed to have satisfied him/herself independently as to the suitability of our products for his/her own particular purpose. In no event shall Rust-Oleum Europe be liable for consequential or incidental damages. Products must be stored, handled, and applied under conditions complying with Rust-Oleum Europe recommendations detailed within the latest copy of the product data sheet. It is the users responsibility to ensure that they have the current copy. Latest copies of the product data sheet is available for free and downloadable from www.rust-oleum.eu or upon a request to our Customer Services department. Rust-Oleum Europe reserves the right to change the properties of its' products without prior notification.

Rust-Oleum Netherlands B.V.

Zilverenberg 16
5234 GM 's-Hertogenbosch
The Netherlands
T: +31 (0) 165 593 636
F: +31 (0) 165 593 600
info@rust-oleum.eu

Tor Coatings Ltd (Rust-Oleum Industrial)

Shadon Way, Portobello Ind. Estate
Birtley, Chester-le-Street
DH3 2RE United Kingdom
T: +44 (0)1914 113 146
F: +44 (0)1914 113 147
info@rust-oleum.eu

Rust-Oleum France S.A.S.

38, av. du Gros Chêne
95322 Herblay
France
T: +33(0) 130 40 00 44
F: +33(0) 130 40 99 80
info@rust-oleum.eu

N.V. Martin Mathys S.A.

Kolenbergstraat 23
3545 Zelem
Belgium
T: +32 (0) 13 460 200
F: +32 (0) 13 460 201
info@rust-oleum.eu