

SAFETY DATA SHEET



6400 Waterbased shopprimer

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : 6400 Waterbased shopprimer
Product description : Paint. Primer
Product type : Liquid.
UFI : QAT0-F054-S00C-YYYY
Product code : ROI0067

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses	
Industrial Professional	
Uses advised against	Reason
Consumer	Product is not intended for consumer use.

1.3 Details of the supplier of the safety data sheet

RUST-OLEUM EUROPE
Martin Mathys NV, Kolenbergstraat 23, B-3545 Zelem, Belgium
Telephone no.: +32 (0) 13 460 200
Fax no.: +32 (0) 13 460 201

Tor Coatings Limited
Unit 21, White Rose Way, Follingsby Park, Gateshead, Tyne & Wear, NE10 8YX United Kingdom
Telephone no.: +44 (0) 191 4106611
Fax no.: +44 (0) 191 4920125
enquiries@tor-coatings.com

e-mail address of person responsible for this SDS : rpmeurohas@rustoleum.eu

1.4 Emergency telephone number

National advisory body/Poison Centre

Supplier

Telephone number United Kingdom: : +44 870 8200418 / +44 2038073798
Great Britain
Hours of operation : 24 / 7

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to UK CLP/GHS

STOT RE 2, H373
Aquatic Chronic 3, H412

The product is classified as hazardous according to UK CLP Regulation SI 2019/720 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

SECTION 2: Hazards identification

2.2 Label elements

Hazard pictograms

:



Signal word

: Warning

Hazard statements

: H373 - May cause damage to organs through prolonged or repeated exposure.
H412 - Harmful to aquatic life with long lasting effects.

Precautionary statements

General

: Not applicable.

Prevention

: P280 - Wear protective gloves.
P260 - Do not breathe vapour or spray.

Response

: Not applicable.

Storage

: Not applicable.

Disposal

: P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.

Hazardous ingredients

: crystalline silica, respirable powder

Supplemental label elements

: EUH208 - Contains reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1) (C(M)IT/MIT (3:1)). May produce an allergic reaction.

Supplemental label elements : Detergents - Regulation (EC) No 907/2006

: Not applicable.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

: Not applicable.

Special packaging requirements

Containers to be fitted with child-resistant fastenings

: Not applicable.

Tactile warning of danger

: Not applicable.

2.3 Other hazards

Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII

: This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

Product meets the criteria for endocrine disrupting properties according to Regulation (EC) No. 1907/2006.

: Not applicable

Other hazards which do not result in classification

: None known.

SECTION 3: Composition/information on ingredients**3.2 Mixtures**

: Mixture

Product/ingredient name	Identifiers	%	Classification	Type
trizinc bis(orthophosphate)	REACH #: 01-2119485044-40 EC: 231-944-3 CAS: 7779-90-0 Index: 030-011-00-6	<2	Aquatic Acute 1, H400 (M=1) Aquatic Chronic 1, H410 (M=1)	[1]
crystalline silica, respirable powder	EC: 238-878-4 CAS: 14808-60-7	≤3	STOT RE 1, H372	[1] [2]
zinc oxide	REACH #: 01-2119463881-32 EC: 215-222-5 CAS: 1314-13-2 Index: 030-013-00-7	<0,5	Aquatic Acute 1, H400 (M=1) Aquatic Chronic 1, H410 (M=1)	[1]
reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1) (C(M)IT/MIT (3:1))	REACH #: 01-2120764691-48 CAS: 55965-84-9 Index: 613-167-00-5	<0,001	Acute Tox. 3, H301 Acute Tox. 2, H310 Acute Tox. 2, H330 Skin Corr. 1C, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 (M=100) Aquatic Chronic 1, H410 (M=100) EUH071 See Section 16 for the full text of the H statements declared above.	[1]

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Type

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures**4.1 Description of first aid measures****Eye contact**

: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention following exposure or if feeling unwell.

Inhalation

: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention following exposure or if feeling unwell. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Skin contact

: Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Continue to rinse for at least 10 minutes. Get medical attention following exposure or if feeling unwell. Wash clothing before reuse. Clean shoes thoroughly before reuse.

SECTION 4: First aid measures

- Ingestion** : Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention following exposure or if feeling unwell. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

4.2 Most important symptoms and effects, both acute and delayed

Over-exposure signs/symptoms

- Eye contact** : No specific data.
- Inhalation** : No specific data.
- Skin contact** : No specific data.
- Ingestion** : No specific data.

4.3 Indication of any immediate medical attention and special treatment needed

- Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
- Specific treatments** : No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

- Suitable extinguishing media** : Use an extinguishing agent suitable for the surrounding fire.
- Unsuitable extinguishing media** : None known.

5.2 Special hazards arising from the substance or mixture

- Hazards from the substance or mixture** : In a fire or if heated, a pressure increase will occur and the container may burst. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
- Hazardous combustion products** : Decomposition products may include the following materials:
carbon dioxide
carbon monoxide
phosphorus oxides
metal oxide/oxides

5.3 Advice for firefighters

- Special protective actions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to British standard BS EN 469 will provide a basic level of protection for chemical incidents.
- Additional information** : No unusual hazard if involved in a fire.

SECTION 6: Accidental release measures**6.1 Personal precautions, protective equipment and emergency procedures**

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
- For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

- 6.2 Environmental precautions** : Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

6.3 Methods and material for containment and cleaning up

- Small spill** : Stop leak if without risk. Move containers from spill area. Absorb with an inert material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
- Large spill** : Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.

- 6.4 Reference to other sections** : See Section 1 for emergency contact information.
See Section 8 for information on appropriate personal protective equipment.
See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance.

7.1 Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Do not breathe vapour or mist. Do not ingest. Avoid contact with eyes, skin and clothing. Avoid release to the environment. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

Do not store below the following temperature: 0°C (32°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

7.3 Specific end use(s)

6400 Waterbased shopprimer

SECTION 7: Handling and storage

Recommendations : Not available.

Industrial sector specific solutions : Not available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

Product/ingredient name	Exposure limit values
crystalline silica, respirable powder	EH40/2005 WELs (United Kingdom (UK), 1/2020) [silica, respirable crystalline] Carc. TWA 8 hours: 0,1 mg/m ³ . Form: Respirable fraction.

Biological exposure indices

No exposure indices known.

Recommended monitoring procedures : Reference should be made to monitoring standards, such as the following: British Standard BS EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) British Standard BS EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) British Standard BS EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

DNELs/DMELs

Product/ingredient name	Result	Value	Effects
trizinc bis(orthophosphate)	DNEL - Workers - Long term - Inhalation	5 mg/m ³	<u>Effects:</u> Systemic
	DNEL - General population - Consumers - Long term - Inhalation	2,5 mg/m ³	<u>Effects:</u> Systemic
	DNEL - Workers - Long term - Dermal	83 mg/kg bw/day	<u>Effects:</u> Systemic
	DNEL - General population - Consumers - Long term - Dermal	83 mg/kg bw/day	<u>Effects:</u> Systemic
zinc oxide	DNEL - General population - Consumers - Long term - Oral	0,83 mg/kg bw/day	<u>Effects:</u> Systemic
	DNEL - Workers - Long term - Inhalation	5 mg/m ³	<u>Effects:</u> Systemic
	DNEL - General population - Consumers - Long term - Inhalation	2,5 mg/m ³	<u>Effects:</u> Systemic
	DNEL - Workers - Long term - Dermal	83 mg/kg bw/day	<u>Effects:</u> Systemic
reaction mass of: 5-chloro-2-methyl-	DNEL - General population - Consumers - Long term - Dermal	83 mg/kg bw/day	<u>Effects:</u> Systemic
	DNEL - General population - Consumers - Long term - Oral	0,83 mg/kg bw/day	<u>Effects:</u> Systemic
	DNEL - Workers - Long term -	0,02 mg/m ³	<u>Effects:</u> Local

6400 Waterbased shopprimer

SECTION 8: Exposure controls/personal protection

4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1) (C(M)IT/MIT (3:1))	Inhalation		
	DNEL - Workers - Short term - Inhalation	0,04 mg/m ³	<u>Effects</u> : Local
	DNEL - General population - Long term - Inhalation	0,02 mg/m ³	<u>Effects</u> : Local
	DNEL - General population - Short term - Inhalation	0,04 mg/m ³	<u>Effects</u> : Local
	DNEL - General population - Long term - Oral	0,09 mg/kg bw/day	<u>Effects</u> : Systemic
	DNEL - General population - Short term - Oral	0,11 mg/kg bw/day	<u>Effects</u> : Systemic

PNECs

Product/ingredient name	Result	Value	Remarks
trizinc bis(orthophosphate)	Fresh water	48,1 µg/l	-
	Marine	14,2 µg/l	-
	Fresh water sediment	550,2 mg/kg	-
	Marine water sediment	263,9 mg/kg	-
	Soil	249,4 mg/kg	-
	Sewage Treatment Plant	121,4 µg/l	-
zinc oxide	Fresh water	25,6 µg/l	-
	Marine	7,6 µg/l	-
	Sewage Treatment Plant	64,7 µg/l	-
	Fresh water sediment	146 mg/kg dwt	-
	Marine water sediment	70,3 mg/kg dwt	-
	Soil	44,3 mg/kg dwt	-
reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1) (C(M)IT/MIT (3:1))	Fresh water	20,6 µg/l	-
	Marine water	6,1 µg/l	-
	Fresh water sediment	117,8 mg/kg	-
	Marine water sediment	56,5 mg/kg	-
	Soil	35,6 mg/kg	-
	Sewage Treatment Plant	100 µg/l	-
	Fresh water	0,00339 mg/l	-
	Marine water	0,00339 mg/l	-
		0,23 mg/l	-

SECTION 8: Exposure controls/personal protection

Sewage Treatment Plant			
	Fresh water sediment	0,027 mg/kg	-
	Marine water sediment	0,027 mg/kg	-
	Soil	0,01 mg/kg	-

8.2 Exposure controls

Appropriate engineering controls : If user operations generate dust, fumes, gas, vapour or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

Individual protection measures

Hygiene measures : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. Use eye protection according to EN 166. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.

Skin protection

There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals.

The breakthrough time must be greater than the end use time of the product.

The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.

Gloves should be replaced regularly and if there is any sign of damage to the glove material.

Always ensure that gloves are free from defects and that they are stored and used correctly.

The performance or effectiveness of the glove may be reduced by physical/chemical damage and poor maintenance. Barrier creams may help to protect the exposed areas of the skin but should not be applied once exposure has occurred.

Hand protection : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. > 8 hours (breakthrough time): nitrile rubber (0.5mm)

The recommendation for the type or types of glove to use when handling this product is based on information from the following source: EN374. The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.

Body protection : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Recommended: (EN 467) Wear overalls or long sleeved shirt.

Other skin protection : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use. Recommended: organic vapour filter (Type A) particulate filter (EN 140)

SECTION 8: Exposure controls/personal protection

Environmental exposure controls : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

Physical state	: Liquid. [Emulsion.]
Colour	: Brownish-red.
Odour	: Ammoniacal. [Slight]
Odour threshold	: Not available.
Melting point/freezing point	: 0°C [Literature (water)]
Initial boiling point and boiling range	: 100°C (212°F) [Literature (water)]
Flammability (solid, gas)	: Non-flammable in the presence of the following materials or conditions: open flames, sparks and static discharge, heat and shocks and mechanical impacts. Non-flammable but will burn on prolonged exposure to flame or high temperature.
Lower and upper explosion limit	: Does not contain sufficient volatile flammable components to form an explosive atmosphere under normal conditions of use.
Flash point	: Not relevant due to nature of the product.
Auto-ignition temperature	: Not relevant due to nature of the product.
Decomposition temperature	: Not applicable.
pH	: 9 [Conc. (% w/w): 100%] [OECD 122]
pH : Justification	: Not available.
Viscosity	: Dynamic (room temperature): 1150 to 1350 mPa·s [ASTM D562 [KU]] Kinematic (room temperature): 920 to 1106 mm ² /s [Calculated] Kinematic (40°C): >20,5 mm ² /s [Calculated]
Solubility(ies)	:

Media	Result
cold water	Soluble
hot water	Soluble
methanol	Very slightly soluble
acetone	Very slightly soluble

Solubility in water	: Not available.
Miscible with water	: Yes.
Partition coefficient: n-octanol/ water	: Not applicable.
Vapour pressure	: 2,3 kPa (17,25 mm Hg) [Literature (water)]
Evaporation rate	: <1 (butyl acetate = 1)
Relative density	: Not available.
Density	: 1,22 to 1,25 g/cm ³ [20°C (68°F)] [DIN 53217]
Vapour density	: >1 [Air = 1]
Explosive properties	: Non-explosive in the presence of the following materials or conditions: open flames, sparks and static discharge and heat. No unusual hazard if involved in a fire.
Oxidising properties	: Not available.
Particle characteristics	
Median particle size	: Not applicable.

SECTION 10: Stability and reactivity

- 10.1 Reactivity** : No specific test data related to reactivity available for this product or its ingredients.
- 10.2 Chemical stability** : The product is stable.
- 10.3 Possibility of hazardous reactions** : Under normal conditions of storage and use, hazardous reactions will not occur.
- 10.4 Conditions to avoid** : No specific data.
- 10.5 Incompatible materials** : No specific data.
- 10.6 Hazardous decomposition products** : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Value
trizinc bis(orthophosphate)	Rat - Oral - LD50	>5000 mg/kg
	Rat - Inhalation - LC50 Dusts and mists	>5,7 mg/l [4 hours]
zinc oxide	Rat - Oral - LD50	>15 g/kg
	Mouse - Inhalation - LC50 Dusts and mists	2500 mg/m ³ [4 hours]
reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1) (C(M)IT/MIT (3:1))	Rabbit - Dermal - LD50	92,4 mg/kg
	Rat - Oral - LD50	64 mg/kg
	Rat - Male, Female - Inhalation - LC50 Dusts and mists	0,171 mg/l [4 hours]

Conclusion/Summary [Product] : Based on available data, the classification criteria are not met.

Ingredient name

reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1) (C(M)IT/MIT (3:1))

Conclusion/Summary

Toxic if swallowed.

Acute toxicity estimates

Product/ingredient name	Oral (mg/kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapours) (mg/l)	Inhalation (dusts and mists) (mg/l)
reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1) (C(M)IT/MIT (3:1))	64	92,4	N/A	N/A	0,171

SECTION 11: Toxicological information**Skin corrosion/irritation**

Product/ingredient name	Result	Exposure	Observation
zinc oxide	Rabbit - Skin - Mild irritant	<u>Amount/concentration applied:</u> 500 mg	-
reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1) (C(M)IT/MIT (3:1))	Human - Skin - Severe irritant	<u>Amount/concentration applied:</u> 0.01 %	-
	Rabbit - Skin - Severe irritant	-	<u>Observation period:</u> 1 to 4 hours

Conclusion/Summary [Product] : Based on available data, the classification criteria are not met.

Ingredient name

crystalline silica, respirable powder
zinc oxide
reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1) (C(M)IT/MIT (3:1))

Conclusion/Summary

Non-irritating to the skin.
Non-irritating to the skin.
Fatal in contact with Skin

Serious eye damage/eye irritation

Product/ingredient name	Result	Exposure	Observation
zinc oxide	Rabbit - Eyes - Mild irritant	<u>Amount/concentration applied:</u> 500 mg	-
reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1) (C(M)IT/MIT (3:1))	Rabbit - Eyes - Severe irritant	-	-

Conclusion/Summary [Product] : Based on available data, the classification criteria are not met.

Ingredient name

crystalline silica, respirable powder
zinc oxide
reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1) (C(M)IT/MIT (3:1))

Conclusion/Summary

Non-irritating to the eyes.
Non-irritating to the eyes.
Risk of serious damage to eyes.

Respiratory corrosion/irritation

Not available.

Conclusion/Summary [Product] : May cause damage to organs through prolonged or repeated exposure.

Ingredient name

reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1) (C(M)IT/MIT (3:1))

Conclusion/Summary

May be fatal if swallowed and enters airways.

Respiratory or skin sensitization

SECTION 11: Toxicological information

Product/ingredient name	Species - Route of exposure	Result
reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1) (C(M)IT/MIT (3:1))	Guinea pig - skin	<u>Result</u> : Sensitising

Skin

Conclusion/Summary [Product] : Based on available data, the classification criteria are not met.

Ingredient name

zinc oxide

Conclusion/Summary

Non-sensitiser to skin.

reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1) (C(M)IT/MIT (3:1))

Strong Skin Sensitizer

Respiratory

Conclusion/Summary [Product] : Based on available data, the classification criteria are not met.

Ingredient name

zinc oxide

Conclusion/Summary

None sensitizer

reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1) (C(M)IT/MIT (3:1))

Based on available data, the classification criteria are not met.

Germ cell mutagenicity

Not available.

Conclusion/Summary [Product] : Based on available data, the classification criteria are not met.

Carcinogenicity

Not available.

Conclusion/Summary [Product] : Based on available data, the classification criteria are not met.

Reproductive toxicity

Not available.

Conclusion/Summary [Product] : Based on available data, the classification criteria are not met.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)**Product/ingredient name**

crystalline silica, respirable powder

Result

STOT RE 1, H372

Aspiration hazard

Not available.

Information on likely routes of exposure

SECTION 11: Toxicological information

Routes of entry anticipated: Oral, Inhalation, Eyes.

Routes of entry not anticipated: Dermal.

Potential acute health effects

- Eye contact** : No known significant effects or critical hazards.
Inhalation : No known significant effects or critical hazards.
Skin contact : No known significant effects or critical hazards.
Ingestion : No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

- Eye contact** : No specific data.
Inhalation : No specific data.
Skin contact : No specific data.
Ingestion : No specific data.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Short term exposure

- Potential immediate effects** : Not available.
Potential delayed effects : Not available.

Long term exposure

- Potential immediate effects** : Not available.
Potential delayed effects : Not available.

Potential chronic health effects

Not available.

Conclusion/Summary [Product] : Based on available data, the classification criteria are not met.

- General** : May cause damage to organs through prolonged or repeated exposure.
Carcinogenicity : No known significant effects or critical hazards.
Mutagenicity : No known significant effects or critical hazards.
Reproductive toxicity : No known significant effects or critical hazards.

Other information

Not available.

SECTION 12: Ecological information

12.1 Toxicity

Product/ingredient name	Result	Species
trizinc bis(orthophosphate)	Acute - IC50 1,87 mg/l [72 hours]	Algae
	Acute - EC50 5,7 mg/l [48 hours]	Daphnia spec.
zinc oxide	Acute - LC50 - Fresh water 98 µg/l [48 hours]	Daphnia spec. - Water flea - Neonate
	Acute - IC50 - Fresh water 46 µg/l [72 hours]	Algae - Green algae - Exponential growth phase
	Acute - EC50 - Fresh water 0,481 mg/l [48 hours]	Daphnia spec. - Water flea - Neonate
	Acute - EC50 0,413 mg/l [48 hours]	Daphnia spec.

SECTION 12: Ecological information

reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1) (C(M)IT/MIT (3:1))	Chronic - NOEC 0,082 mg/l [7 days]	Daphnia spec.
	Acute - EC50 0,137 mg/l [72 hours]	Algae
	Chronic - NOEC 0,019 mg/l [7 days]	Algae
	Acute - LC50 0,33 to 0,78 mg/l [96 hours]	Fish - Rainbow trout (oncorhynchus mykiss)
	Acute - EC50 0,024 mg/l [72 hours]	Algae
	Chronic - NOEC 0,199 mg/l [30 days]	Fish - Rainbow trout (oncorhynchus mykiss)
	Chronic - NOEC 0,037 mg/l [21 days]	Daphnia spec.
	Acute - EC50 - Fresh water 0,037 mg/l [48 hours]	Algae
	Chronic - NOEC 0,18 mg/l [21 days]	Daphnia spec. - Daphnia spec.
	Acute - EC50 - Fresh water 0,16 mg/l [48 hours]	Daphnia spec.
Acute - LC50 - Fresh water 0,19 mg/l [96 hours]	Fish - Rainbow trout (oncorhynchus mykiss)	
Acute - NOEC - Marine water 0,004 mg/l [48 hours]	Algae	
Chronic - NOEC - Fresh water 0,02 mg/l [38 days]	Fish - Rainbow trout (oncorhynchus mykiss)	

Conclusion/Summary [Product] : Harmful to aquatic life with long lasting effects.

12.2 Persistence and degradability

Product/ingredient name	Test	Result
reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1) (C(M)IT/MIT (3:1))	-	>60% [28 days] - Readily
	-	<50% [10 days]

Conclusion/Summary [Product] : This product has not been tested for biodegradation. Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
zinc oxide	-	-	Not readily
reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1) (C(M)IT/MIT (3:1))	-	-	Inherent

12.3 Bioaccumulative potential

Product/ingredient name	LogP _{ow}	BCF	Potential
trizinc bis(orthophosphate)	-	60960	High
zinc oxide	-	28960	High
reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1) (C(M)IT/MIT (3:1))	-0.83 to 0.75	-	Low

12.4 Mobility in soil

Soil/water partition coefficient : Not available.

Mobility : Nonvolatile liquid.

12.5 Results of PBT and vPvB assessment

Product/ingredient name	PBT	P	B	T	vPvB	vP	vB
trizinc bis(orthophosphate)	No	No	No	No	No	No	No
crystalline silica, respirable powder	No	No	No	No	No	No	No
zinc oxide	No	No	No	No	No	No	No
reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1) (C(M)IT/MIT (3:1))	N/A	N/A	N/A	Yes	N/A	N/A	N/A

12.6 Other adverse effects : No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance.

13.1 Waste treatment methods**Product**

Methods of disposal : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

Hazardous waste : Yes.

Waste catalogue

6400 Waterbased shopprimer

SECTION 13: Disposal considerations

Waste code	Waste designation
08 01 15*	aqueous sludges containing paint or varnish containing organic solvents or other hazardous substances

Special precautions : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

	ADR/RID	ADN	IMDG	IATA
14.1 UN number or ID number	Not regulated.	Not regulated.	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	-	-	-
14.3 Transport hazard class(es)	-	-	-	-
14.4 Packing group	-	-	-	-
14.5 Environmental hazards	No.	No.	No.	No.

Additional information ADR

Additional information ADN

Additional information IMDG

Additional information IATA

14.6 Special precautions for user : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Maritime transport in bulk according to IMO instruments : Not available.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

UK (GB)/REACH

Annex XIV - List of substances subject to authorisation

Annex XIV

None of the components are listed above the relevant limit.

Substances of very high concern

None of the components are listed above the relevant limit.

SECTION 15: Regulatory information

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Product/ingredient name	%	Designation [Usage]
6400 Waterbased shopprimer	≥90	3

Labelling : Not applicable.

Synthetic polymer microparticles - Designation 78

Generic identity of polymer(s) : Not applicable.

Total percentage of synthetic polymer microparticles : Not applicable.

Other EU regulations

VOC : The provisions of Directive 2004/42/EC on VOC apply to this product. Refer to the product label and/or technical data sheet for further information.

VOC for Ready-for-Use Mixture : 2004/42/EC - IIA/i: 140g/l (2010). ≤ 13g/l VOC.

Industrial emissions (integrated pollution prevention and control) - Air : Not listed

Industrial emissions (integrated pollution prevention and control) - Water : Not listed

Ozone depleting substances

Not listed.

Prior Informed Consent (PIC)

Not listed.

Persistent Organic Pollutants

Not listed.

Seveso Directive

This product is not controlled under the Seveso Directive.

National regulations

Product/ingredient name	List name	Name on list	Classification	Notes
crystalline silica, respirable powder	EH40/2005 WELs	silica, respirable crystalline	Carc	-

EU regulations

Industrial emissions (integrated pollution prevention and control) - Air : Not listed

Industrial emissions (integrated pollution prevention and control) - Water : Not listed

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

Montreal Protocol

SECTION 15: Regulatory information

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

CN code : 3209 10 00 00**Inventory list**

Australia	: Not determined.
Canada	: At least one component is not listed.
China	: Not determined.
Eurasian Economic Union	: Russian Federation inventory : Not determined.
Japan	: Japan inventory (CSCL) : Not determined. Japan inventory (ISHL) : At least one component is not listed.
New Zealand	: Not determined.
Philippines	: Not determined.
Republic of Korea	: Not determined.
Taiwan	: Not determined.
Thailand	: Not determined.
Turkey	: Not determined.
United States	: Not determined.
Viet Nam	: Not determined.

15.2 Chemical safety assessment : This product contains substances for which Chemical Safety Assessments are still required.**SECTION 16: Other information**

✔ Indicates information that has changed from previously issued version.

Abbreviations and acronyms	: ATE = Acute Toxicity Estimate GB CLP = UK CLP (EC No 1272/2008) on the Classification, Labelling and Packaging of Substances and Mixtures as amended by (EU Exit) Regulations 2019 No. 720 and amendments DMEL = Derived Minimal Effect Level DNEL = Derived No Effect Level EUH statement = GB CLP-specific Hazard statement N/A = Not available PBT = Persistent, Bioaccumulative and Toxic PNEC = Predicted No Effect Concentration RRN = REACH Registration Number SGG = Segregation Group vPvB = Very Persistent and Very Bioaccumulative
-----------------------------------	--

Procedure used to derive the classification

Classification	Justification
STOT RE 2, H373 Aquatic Chronic 3, H412	Calculation method Calculation method

Full text of abbreviated H statements

SECTION 16: Other information

H301	Toxic if swallowed.
H310	Fatal in contact with skin.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H330	Fatal if inhaled.
H372	Causes damage to organs through prolonged or repeated exposure.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH071	Corrosive to the respiratory tract.

Full text of classifications

Acute Tox. 2	ACUTE TOXICITY - Category 2
Acute Tox. 3	ACUTE TOXICITY - Category 3
Aquatic Acute 1	SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1
Aquatic Chronic 1	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1
Aquatic Chronic 3	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3
Eye Dam. 1	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1
Skin Corr. 1C	SKIN CORROSION/IRRITATION - Category 1C
Skin Sens. 1A	SKIN SENSITISATION - Category 1A
STOT RE 1	SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 1
STOT RE 2	SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 2

Date of printing : 26/11/2025

Date of issue/ Date of revision : 26/11/2025

Date of previous issue : 25/05/2023

Version : 9

Notice to reader

IMPORTANT NOTE: The information in this Safety Data Sheet is based on the present state of knowledge and current legislation. It provides guidance on health, safety and environmental aspects of the product and should not be construed as any guarantee of technical performance or suitability for particular applications. The information contained in this data sheet (as may be amended from time to time) is not intended to be exhaustive and is presented in good faith and believed to be correct as of the date on which it is prepared. It is the user's responsibility to verify that this data sheet is current prior to using the product to which it relates. Persons using the information must make their own determinations as to the suitability of the relevant product for their purposes prior to use. Where those purposes are other than as specifically recommended in this safety data sheet, then the user uses the product at their own risk.

MANUFACTURER'S DISCLAIMER: the conditions, methods and factors affecting the handling, storage, application, use and disposal of the product are not under the control and knowledge of the manufacturer. Therefore the manufacturer does not assume responsibility for any adverse events which may occur in the handling, storage, application, use, misuse or disposal of the product and, so far as permitted by applicable law, the manufacturer expressly disclaims liability for any and all loss, damages and/or expenses arising out of or in any way connected to the storage, handling, use or disposal of the product. Safe handling, storage, use and disposal are the responsibility of the users. Users must comply with all applicable health and safety laws.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.