

SAFETY DATA SHEET



7300 CombiColor Original Wrought Iron

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : 7300 CombiColor Original Wrought Iron
Product description : Paint
Product type : Liquid.
UFI : N9A2-90Q9-A002-TQR5
Product code : ROI0074

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses	
<input checked="" type="checkbox"/> Consumer <input type="checkbox"/> Industrial <input type="checkbox"/> Professional	
Uses advised against	Reason
None identified.	-

1.3 Details of the supplier of the safety data sheet

RUST-OLEUM EUROPE
Martin Mathys NV, Kolenbergstraat 23, B-3545 Zelem, Belgium
Telephone no.: +32 (0) 13 460 200
Fax no.: +32 (0) 13 460 201

Tor Coatings Limited
Unit 21, White Rose Way, Follingsby Park, Gateshead, Tyne & Wear, NE10 8YX United Kingdom
Telephone no.: +44 (0) 191 4106611
Fax no.: +44 (0) 191 4920125
enquiries@tor-coatings.com

e-mail address of person responsible for this SDS : rpmeurohas@rustoleum.eu

1.4 Emergency telephone number

National advisory body/Poison Centre

Supplier

Telephone number United Kingdom: : +44 870 8200418 / +44 2038073798
Great Britain
Hours of operation : 24 / 7

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to UK CLP/GHS

Flam. Liq. 3, H226
STOT SE 3, H336
Aquatic Chronic 3, H412

The product is classified as hazardous according to UK CLP Regulation SI 2019/720 as amended.


SECTION 2: Hazards identification

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Hazard pictograms



Signal word

: Warning

Hazard statements

: H226 - Flammable liquid and vapour.
H336 - May cause drowsiness or dizziness.
H412 - Harmful to aquatic life with long lasting effects.

Precautionary statements

General

: P103 - Read carefully and follow all instructions.
P102 - Keep out of reach of children.
P101 - If medical advice is needed, have product container or label at hand.

Prevention

: P280 - Wear protective gloves.
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P271 - Use only outdoors or in a well-ventilated area.

Response

: P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.

Storage

: P403 + P235 - Store in a well-ventilated place. Keep cool.

Disposal

: P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.

Hazardous ingredients

: Hydrocarbons, C9-C11, n-/ iso-/ cyclo-alkanes, < 2% aromatics

Supplemental label elements

: EUH066 - Repeated exposure may cause skin dryness or cracking.
EUH208 - Contains phthalic anhydride and neodecanoic acid, cobalt salt. May produce an allergic reaction.

Supplemental label elements : Detergents - Regulation (EC) No 907/2006

: Not applicable.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

: Not applicable.

Special packaging requirements

Containers to be fitted with child-resistant fastenings

: Not applicable.

Tactile warning of danger

: Not applicable.

2.3 Other hazards

Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII

: This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

Product meets the criteria for endocrine disrupting properties according to Regulation (EC) No. 1907/2006.

: Not applicable

SECTION 2: Hazards identification

Other hazards which do not result in classification : None known.

SECTION 3: Composition/information on ingredients

3.2 Mixtures : Mixture

Product/ingredient name	Identifiers	%	Classification	Type
Hydrocarbons, C9-C11, n-/ iso-/ cyclo-alkanes, < 2% aromatics	REACH #: 01-2119463258-33 EC: 919-857-5	≥25 - ≤50	Flam. Liq. 3, H226 STOT SE 3, H336 Asp. Tox. 1, H304 EUH066	[1] [2]
hydrocarbons, C10-C13, n-/ iso-/ cyclo-alkanes, < 2% aromatics	REACH #: 01-2119457273-39 EC: 918-481-9	≤3	Asp. Tox. 1, H304 EUH066	[1] [2]
trizinc bis(orthophosphate)	REACH #: 01-2119485044-40 EC: 231-944-3 CAS: 7779-90-0 Index: 030-011-00-6	≤1	Aquatic Acute 1, H400 (M=1) Aquatic Chronic 1, H410 (M=1)	[1]
zinc oxide	REACH #: 01-2119463881-32 EC: 215-222-5 CAS: 1314-13-2 Index: 030-013-00-7	≤0,3	Aquatic Acute 1, H400 (M=1) Aquatic Chronic 1, H410 (M=1)	[1]
phthalic anhydride	REACH #: 01-2119457017-41 EC: 201-607-5 CAS: 85-44-9 Index: 607-009-00-4	≤0,3	Acute Tox. 4, H302 Skin Irrit. 2, H315 Eye Dam. 1, H318 Resp. Sens. 1, H334 Skin Sens. 1, H317 STOT SE 3, H335	[1] [2]
neodecanoic acid, cobalt salt	REACH #: 01-2119970733-31 EC: 248-373-0 CAS: 27253-31-2	≤0,3	Acute Tox. 4, H302 Skin Sens. 1, H317 STOT RE 1, H372 Aquatic Chronic 3, H412 See Section 16 for the full text of the H statements declared above.	[1] [2]

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Type

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures**4.1 Description of first aid measures**

Eye contact : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.

Inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or

SECTION 4: First aid measures

- waistband.
- Skin contact** : Wash skin thoroughly with soap and water or use recognised skin cleanser. Remove contaminated clothing and shoes. Get medical attention if symptoms occur. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion** : Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. If necessary, call a poison center or physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

4.2 Most important symptoms and effects, both acute and delayed**Over-exposure signs/symptoms**

- Eye contact** : No specific data.
- Inhalation** : Adverse symptoms may include the following:
nausea or vomiting
headache
drowsiness/fatigue
dizziness/vertigo
unconsciousness
- Skin contact** : Adverse symptoms may include the following:
irritation
dryness
cracking
- Ingestion** : No specific data.

4.3 Indication of any immediate medical attention and special treatment needed

- Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
- Specific treatments** : No specific treatment.

SECTION 5: Firefighting measures**5.1 Extinguishing media**

- Suitable extinguishing media** : Use dry chemical, CO₂, water spray (fog) or foam.
- Unsuitable extinguishing media** : Do not use water jet.

5.2 Special hazards arising from the substance or mixture

- Hazards from the substance or mixture** : Flammable liquid and vapour. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. The vapour/gas is heavier than air and will spread along the ground. Vapours may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

SECTION 5: Firefighting measures

Hazardous combustion products : Decomposition products may include the following materials:
 carbon dioxide
 carbon monoxide
 metal oxide/oxides

5.3 Advice for firefighters

Special protective actions for fire-fighters : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

Special protective equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to British standard BS EN 469 will provide a basic level of protection for chemical incidents.

Additional information : No unusual hazard if involved in a fire.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

6.2 Environmental precautions

: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

6.3 Methods and material for containment and cleaning up

Small spill : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Absorb with an inert material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.

6.4 Reference to other sections

: See Section 1 for emergency contact information.
 See Section 8 for information on appropriate personal protective equipment.
 See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance.

7.1 Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapour or mist. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by earthing and bonding containers and equipment before transferring material. Empty containers retain product residue and can be hazardous. Do not reuse container.
- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

Do not store above the following temperature: 35°C (95°F). Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidising materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Seveso Directive - Reporting thresholds

Danger criteria

Category	Notification and MAPP threshold	Safety report threshold
P5c	5000 tonnes	50000 tonnes

7.3 Specific end use(s)

- Recommendations** : Not available.
- Industrial sector specific solutions** : Not available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

Product/ingredient name	Exposure limit values
hydrocarbons, C9-C11, n-/ iso-/ cyclo-alkanes, < 2% aromatics	Recommended by manufacturer (GB, 2009) [hydrocarbons, C9-C11, n-/ iso-/ cyclo-alkanes, < 2% aromatics] TWA 8 hours: 1200 mg/m ³ (as hydrocarbon mixture (A) (197 ppm)). Form: Vapour.
hydrocarbons, C10-C13, n-/ iso-/ cyclo-alkanes, < 2% aromatics	Recommended by manufacturer (GB, 2009) [hydrocarbons, C10-C13, n-/ iso-/ cyclo-alkanes, < 2% aromatics] TWA 8 hours: 1200 mg/m ³ ((184 ppm)). Form: Vapour.
phthalic anhydride	EH40/2005 WELs (United Kingdom (UK), 1/2020) Inhalation sensitiser. STEL 15 minutes: 12 mg/m ³ . TWA 8 hours: 4 mg/m ³ .
neodecanoic acid, cobalt salt	EH40/2005 WELs (United Kingdom (UK), 1/2020) [cobalt and

SECTION 8: Exposure controls/personal protection

cobalt compounds] Carc. Inhalation sensitiser.
TWA 8 hours: 0,1 mg/m³ (as Co).

Biological exposure indices

No exposure indices known.

Recommended monitoring procedures : Reference should be made to monitoring standards, such as the following: British Standard BS EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) British Standard BS EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) British Standard BS EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

DNELs/DMELs

Product/ingredient name	Result	Value	Effects	
hydrocarbons, C9-C11, n-/ iso-/ cyclo-alkanes, < 2% aromatics	DNEL - Workers - Long term - Dermal	280 mg/kg	Effects: Systemic	
	DNEL - Workers - Short term - Inhalation	871 mg/m ³	Effects: Systemic	
	DNEL - General population - Consumers - Long term - Oral	125 mg/kg bw/day	Effects: Systemic	
	DNEL - General population - Consumers - Long term - Inhalation	185 mg/m ³	Effects: Systemic	
	DNEL - General population - Consumers - Long term - Dermal	125 mg/kg	Effects: Systemic	
	trizinc bis(orthophosphate)	DNEL - Workers - Long term - Inhalation	5 mg/m ³	Effects: Systemic
		DNEL - General population - Consumers - Long term - Inhalation	2,5 mg/m ³	Effects: Systemic
		DNEL - Workers - Long term - Dermal	83 mg/kg bw/day	Effects: Systemic
		DNEL - General population - Consumers - Long term - Dermal	83 mg/kg bw/day	Effects: Systemic
	zinc oxide	DNEL - General population - Consumers - Long term - Oral	0,83 mg/kg bw/day	Effects: Systemic
DNEL - Workers - Long term - Inhalation		5 mg/m ³	Effects: Systemic	
DNEL - General population - Consumers - Long term - Inhalation		2,5 mg/m ³	Effects: Systemic	
DNEL - Workers - Long term - Dermal		83 mg/kg bw/day	Effects: Systemic	
	DNEL - General population - Consumers - Long term -	83 mg/kg bw/day	Effects: Systemic	

SECTION 8: Exposure controls/personal protection

	Dermal		
phthalic anhydride	DNEL - General population - Consumers - Long term - Oral	0,83 mg/kg bw/day	Effects: Systemic
	DNEL - General population - Long term - Oral	5 mg/kg bw/day	Effects: Systemic
	DNEL - General population - Long term - Dermal	5 mg/kg bw/day	Effects: Systemic
	DNEL - General population - Long term - Inhalation	8,7 mg/m ³	Effects: Systemic
	DNEL - Workers - Long term - Dermal	14 mg/kg bw/day	Effects: Systemic
	DNEL - General population - Short term - Oral	25 mg/kg bw/day	Effects: Systemic
neodecanoic acid, cobalt salt	DNEL - Workers - Long term - Inhalation	49,4 mg/m ³	Effects: Systemic
	DNEL - Workers - Long term - Inhalation	273 µg/m ³	Effects: Local
	DNEL - General population - Long term - Inhalation	43 µg/m ³	Effects: Local
	DNEL - General population - Long term - Oral	0,032 mg/kg bw/day	Effects: Systemic

PNECs

Product/ingredient name	Result	Value	Remarks	
trizinc bis(orthophosphate)	Fresh water	48,1 µg/l	-	
	Marine	14,2 µg/l	-	
	Fresh water sediment	550,2 mg/kg	-	
	Marine water sediment	263,9 mg/kg	-	
	Soil	249,4 mg/kg	-	
	Sewage Treatment Plant	121,4 µg/l	-	
	zinc oxide	Fresh water	25,6 µg/l	-
		Marine	7,6 µg/l	-
		Sewage Treatment Plant	64,7 µg/l	-
		Fresh water sediment	146 mg/kg dwt	-
		Marine water sediment	70,3 mg/kg dwt	-
		Soil	44,3 mg/kg dwt	-
		Fresh water	20,6 µg/l	-
		Marine water	6,1 µg/l	-
		Fresh water sediment	117,8 mg/kg	-

SECTION 8: Exposure controls/personal protection

phthalic anhydride	Marine water sediment	56,5 mg/kg	-
	Soil	35,6 mg/kg	-
	Sewage Treatment Plant	100 µg/l	-
	Fresh water	1 mg/l	-
	Marine water	0,1 mg/l	-
	Sewage Treatment Plant	10 mg/l	-
	Fresh water sediment	3,8 mg/kg dwt	-
	Marine water sediment	0,38 mg/kg dwt	-
neodecanoic acid, cobalt salt	Soil	0,173 mg/kg dwt	-
	Fresh water	1,06 µg/l	-
	Marine water	2,36 µg/l	-
	Sewage Treatment Plant	0,37 mg/l	-
	Fresh water sediment	53,8 mg/kg dwt	-
	Marine water sediment	69,8 mg/kg dwt	-
	Soil	10,9 mg/kg dwt	-

8.2 Exposure controls

Appropriate engineering controls : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Individual protection measures

Hygiene measures : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. Use eye protection according to EN 166. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.

Skin protection

There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals.

The breakthrough time must be greater than the end use time of the product.

The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.

Gloves should be replaced regularly and if there is any sign of damage to the glove material.

Always ensure that gloves are free from defects and that they are stored and used correctly.

The performance or effectiveness of the glove may be reduced by physical/chemical damage and poor maintenance.

Barrier creams may help to protect the exposed areas of the skin but should not be applied once exposure has occurred.

SECTION 8: Exposure controls/personal protection

- Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. > 8 hours (breakthrough time): polyethylene (PE), polyvinyl alcohol (PVA), nitrile rubber (0.5mm)
- The recommendation for the type or types of glove to use when handling this product is based on information from the following source: EN374. The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.
- Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves. Refer to British Standard BS EN 1149 for further information on material and design requirements and test methods. Recommended: Personnel should wear antistatic clothing made of natural fibres or of high-temperature-resistant synthetic fibres.
- Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Respiratory protection** : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use. Recommended: organic vapour (Type A) and particulate filter (EN 140)
- Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

- Physical state** : Liquid.
- Colour** : Various
- Odour** : Hydrocarbon. [Slight]
- Odour threshold** : Not available.
- Melting point/freezing point** : Not applicable.
- Initial boiling point and boiling range** : 150 to 205°C (302 to 401°F) [Literature hydrocarbons, C9-C11, n-/ iso-/ cyclo-alkanes, < 2% aromatics]
- Flammability (solid, gas)** : Flammable in the presence of the following materials or conditions: open flames, sparks and static discharge, heat and shocks and mechanical impacts. Vapour may travel a considerable distance to source of ignition and flash back.
- Lower and upper explosion limit** : Lower: 0,6% [Calculated (Le Chatelier mixture rule)]
Upper: 7% [Calculated (Le Chatelier mixture rule)]
- Flash point** : Closed cup: 41°C (105,8°F) [Literature hydrocarbons, C9-C11, n-/ iso-/ cyclo-alkanes, < 2% aromatics]
- Auto-ignition temperature** : >230°C (>446°F) [Literature hydrocarbons, C9-C11, n-/ iso-/ cyclo-alkanes, < 2% aromatics]
- Decomposition temperature** : Not applicable.
- pH** : Not applicable.
- pH : Justification** : Product is non-soluble (in water).

SECTION 9: Physical and chemical properties

Viscosity : Dynamic (room temperature): 1400 to 1500 mPa·s [ASTM D562 [KU]]
Kinematic (room temperature): 1029 to 1163 mm²/s [calculated.]
Kinematic (40°C): >20,5 mm²/s [calculated.]

Solubility(ies) :

Media	Result
cold water	Not soluble
hot water	Not soluble

Solubility in water : Not available.

Partition coefficient: n-octanol/ water : Not applicable.

Vapour pressure : 0,1 to 0,3 kPa (0,75 to 2,25 mm Hg) [Literature hydrocarbons, C9-C11, n-/ iso-/ cyclo-alkanes, < 2% aromatics]

Evaporation rate : 0,2 (Butyl acetate. = 1)

Relative density : Not available.

Density : 1,29 to 1,36 g/cm³ [20°C (68°F)] [DIN 53217]

Vapour density : >1 [Air = 1]

Explosive properties : Non-explosive in the presence of the following materials or conditions: open flames, sparks and static discharge, heat and shocks and mechanical impacts. No unusual hazard if involved in a fire.

Oxidising properties : Not available.

Particle characteristics

Median particle size : Not applicable.

SECTION 10: Stability and reactivity

10.1 Reactivity : No specific test data related to reactivity available for this product or its ingredients.

10.2 Chemical stability : The product is stable.

10.3 Possibility of hazardous reactions : Under normal conditions of storage and use, hazardous reactions will not occur.

10.4 Conditions to avoid : Avoid all possible sources of ignition (spark or flame). Do not pressurise, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition. Do not allow vapour to accumulate in low or confined areas.

10.5 Incompatible materials : Reactive or incompatible with the following materials:
oxidising materials

10.6 Hazardous decomposition products : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information**11.1 Information on toxicological effects****Acute toxicity**

SECTION 11: Toxicological information

Product/ingredient name	Result	Value
hydrocarbons, C10-C13, n-/ iso-/ cyclo-alkanes, < 2% aromatics	Rabbit - Dermal - LD50	>5000 mg/kg
	Rat - Oral - LD50	>5000 mg/kg
	Rat - Inhalation - LC50 Vapour	5000 mg/m ³ [4 hours]
trizinc bis(orthophosphate)	Rat - Oral - LD50	>5000 mg/kg
	Rat - Inhalation - LC50 Dusts and mists	>5,7 mg/l [4 hours]
zinc oxide	Rat - Oral - LD50	>15 g/kg
	Mouse - Inhalation - LC50 Dusts and mists	2500 mg/m ³ [4 hours]
phthalic anhydride	Rat - Oral - LD50	1530 mg/kg
neodecanoic acid, cobalt salt	Rat - Female - Oral - LD50	1098 mg/kg

Conclusion/Summary [Product] : Based on available data, the classification criteria are not met.

Acute toxicity estimates

Product/ingredient name	Oral (mg/kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapours) (mg/l)	Inhalation (dusts and mists) (mg/l)
hydrocarbons, C9-C11, n-/ iso-/ cyclo-alkanes, < 2% aromatics	10000	N/A	N/A	N/A	N/A
phthalic anhydride	1530	N/A	N/A	N/A	N/A
neodecanoic acid, cobalt salt	1098	N/A	N/A	N/A	N/A

Skin corrosion/irritation

Product/ingredient name	Result	Exposure	Observation
zinc oxide	Rabbit - Skin - Mild irritant	Amount/concentration applied: 500 mg	-

Conclusion/Summary [Product] : Based on available data, the classification criteria are not met.

Ingredient name

hydrocarbons, C9-C11, n-/ iso-/ cyclo-alkanes, < 2% aromatics
zinc oxide
neodecanoic acid, cobalt salt

Conclusion/Summary

May cause mild skin irritation
Non-irritating to the skin.
Non-irritating to the skin.

Serious eye damage/eye irritation

Product/ingredient name	Result	Exposure	Observation
zinc oxide	Rabbit - Eyes - Mild irritant	Amount/concentration applied: 500 mg	-
phthalic anhydride	Rabbit - Eyes - Moderate irritant	Amount/concentration applied: 50 mg	-

Conclusion/Summary [Product] : Based on available data, the classification criteria are not met.

SECTION 11: Toxicological information

Ingredient name

hydrocarbons, C9-C11, n-/ iso-/ cyclo-alkanes, < 2% aromatics
zinc oxide
neodecanoic acid, cobalt salt

Conclusion/Summary

Non-irritating to the eyes.
Non-irritating to the eyes.
Non-irritating to the eyes.

Respiratory corrosion/irritation

Not available.

Conclusion/Summary [Product] : May cause drowsiness or dizziness.

Respiratory or skin sensitization

Product/ingredient name	Species - Route of exposure	Result
hydrocarbons, C9-C11, n-/ iso-/ cyclo-alkanes, < 2% aromatics	Rabbit - skin	<u>Result:</u> Not sensitizing

Skin

Conclusion/Summary [Product] : Based on available data, the classification criteria are not met.

Ingredient name

zinc oxide
neodecanoic acid, cobalt salt

Conclusion/Summary

Non-sensitiser to skin.
May cause sensitisation by skin contact.

Respiratory

Conclusion/Summary [Product] : Based on available data, the classification criteria are not met.

Ingredient name

zinc oxide

Conclusion/Summary

None sensitizor

Germ cell mutagenicity

Not available.

Conclusion/Summary [Product] : Based on available data, the classification criteria are not met.

Carcinogenicity

Not available.

Conclusion/Summary [Product] : Based on available data, the classification criteria are not met.

Reproductive toxicity

Not available.

Conclusion/Summary [Product] : Based on available data, the classification criteria are not met.

Specific target organ toxicity (single exposure)

Product/ingredient name

hydrocarbons, C9-C11, n-/ iso-/ cyclo-alkanes, < 2% aromatics
phthalic anhydride

Result

STOT SE 3, H336 (Narcotic effects)
STOT SE 3, H335 (Respiratory tract irritation)

SECTION 11: Toxicological information**Specific target organ toxicity (repeated exposure)**

Product/ingredient name	Result
neodecanoic acid, cobalt salt	STOT RE 1, H372

Aspiration hazard

Product/ingredient name	Result
Hydrocarbons, C9-C11, n-/ iso-/ cyclo-alkanes, < 2% aromatics	ASPIRATION HAZARD - Category 1
hydrocarbons, C10-C13, n-/ iso-/ cyclo-alkanes, < 2% aromatics	ASPIRATION HAZARD - Category 1

Information on likely routes of exposure

Routes of entry anticipated: Oral, Dermal, Inhalation, Eyes.

Potential acute health effects

Eye contact	: No known significant effects or critical hazards.
Inhalation	: Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness.
Skin contact	: Defatting to the skin. May cause skin dryness and irritation.
Ingestion	: Can cause central nervous system (CNS) depression.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact	: No specific data.
Inhalation	: Adverse symptoms may include the following: nausea or vomiting headache drowsiness/fatigue dizziness/vertigo unconsciousness
Skin contact	: Adverse symptoms may include the following: irritation dryness cracking
Ingestion	: No specific data.

Delayed and immediate effects as well as chronic effects from short and long-term exposure**Short term exposure**

Potential immediate effects	: Not available.
Potential delayed effects	: Not available.

Long term exposure

Potential immediate effects	: Not available.
Potential delayed effects	: Not available.

Potential chronic health effects

Not available.

Conclusion/Summary [Product] : Not available.

General	: Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis.
Carcinogenicity	: No known significant effects or critical hazards.
Mutagenicity	: No known significant effects or critical hazards.
Reproductive toxicity	: No known significant effects or critical hazards.

Other information

Not available.

SECTION 12: Ecological information

12.1 Toxicity

Product/ingredient name	Result	Species
hydrocarbons, C9-C11, n-/ iso-/ cyclo-alkanes, < 2% aromatics	Acute - NOEC 100 mg/l [72 hours]	Algae
	Chronic - NOEC 0,23 mg/l	Daphnia spec.
hydrocarbons, C10-C13, n-/ iso-/ cyclo-alkanes, < 2% aromatics	Chronic - NOEC 0,131 mg/l	Fish
	Acute - LC50 >1000 mg/l [4 hours]	Fish
	Acute - EC50 >1000 mg/l [4 hours]	Daphnia spec.
trizinc bis(orthophosphate)	Acute - IC50 >1000 mg/l [4 hours]	Algae
	Acute - IC50 1,87 mg/l [72 hours]	Algae
	Acute - EC50 5,7 mg/l [48 hours]	Daphnia spec.
zinc oxide	Acute - LC50 - Fresh water 98 µg/l [48 hours]	Daphnia spec. - Water flea - Neonate
	Acute - IC50 - Fresh water 46 µg/l [72 hours]	Algae - Green algae - Exponential growth phase
	Acute - EC50 - Fresh water 0,481 mg/l [48 hours]	Daphnia spec. - Water flea - Neonate
	Acute - EC50 0,413 mg/l [48 hours]	Daphnia spec.
	Chronic - NOEC 0,082 mg/l [7 days]	Daphnia spec.
	Acute - EC50 0,137 mg/l [72 hours]	Algae
	Chronic - NOEC 0,019 mg/l [7 days]	Algae
	Acute - LC50 0,33 to 0,78 mg/l [96 hours]	Fish - Rainbow trout (oncorhynchus mykiss)
	Acute - EC50 0,024 mg/l [72 hours]	Algae
	Chronic - NOEC 0,199 mg/l [30 days]	Fish - Rainbow trout (oncorhynchus mykiss)
phthalic anhydride	Chronic - NOEC 0,037 mg/l [21 days]	Daphnia spec.
	Acute - EC50 - Fresh water 78,53 mg/l [96 hours]	Algae - Green algae

SECTION 12: Ecological information

Conclusion/Summary [Product] : Harmful to aquatic life with long lasting effects.

Ingredient name

neodecanoic acid, cobalt salt

Conclusion/Summary

Harmful to aquatic life with long lasting effects.

12.2 Persistence and degradability

Product/ingredient name	Test	Result
hydrocarbons, C9-C11, n-/ iso-/ cyclo-alkanes, < 2% aromatics	-	>80% [28 days] - Readily
	-	>80% [28 days] - Readily

Conclusion/Summary [Product] : This product has not been tested for biodegradation.

Ingredient name

hydrocarbons, C9-C11, n-/ iso-/ cyclo-alkanes, < 2% aromatics

hydrocarbons, C10-C13, n-/ iso-/ cyclo-alkanes, < 2% aromatics

Conclusion/Summary

Rapidly lost by degradation and volatilisation.

Rapidly lost by degradation and volatilisation.

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
hydrocarbons, C9-C11, n-/ iso-/ cyclo-alkanes, < 2% aromatics	-	100%; <28 day(s)	Readily
hydrocarbons, C10-C13, n-/ iso-/ cyclo-alkanes, < 2% aromatics	<28 days [Fresh water] [5 to 25 °C]	80%; <28 day(s)	Readily
zinc oxide	-	-	Not readily

12.3 Bioaccumulative potential

Product/ingredient name	LogP _{ow}	BCF	Potential
hydrocarbons, C9-C11, n-/ iso-/ cyclo-alkanes, < 2% aromatics	5 to 6.7	10 to 2500	High
trizinc bis(orthophosphate)	-	60960	High
zinc oxide	-	28960	High
phthalic anhydride	1,6	3,4	Low
neodecanoic acid, cobalt salt	-	15600	High

12.4 Mobility in soil

Soil/water partition coefficient : Not available.

Mobility : Volatile.

12.5 Results of PBT and vPvB assessment

SECTION 12: Ecological information

Product/ingredient name	PBT	P	B	T	vPvB	vP	vB
hydrocarbons, C9-C11, n-/iso-/ cyclo-alkanes, < 2% aromatics	No	N/A	No	No	No	N/A	No
hydrocarbons, C10-C13, n-/iso-/ cyclo-alkanes, < 2% aromatics	No	No	N/A	No	No	No	N/A
trizinc bis(orthophosphate)	No	No	No	No	No	No	No
zinc oxide	No	No	No	No	No	No	No
phthalic anhydride	No	N/A	No	No	No	N/A	No
neodecanoic acid, cobalt salt	N/A	N/A	Yes	Yes	N/A	N/A	Yes

12.6 Other adverse effects : No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance.

13.1 Waste treatment methods

Product

Methods of disposal : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.





Hazardous waste : Yes.

Waste catalogue

Waste code	Waste designation
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances

Special precautions : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapour from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

	ADR/RID	ADN	IMDG	IATA
14.1 UN number or ID number	UN1263	UN1263	UN1263	UN1263
14.2 UN proper shipping name	PAINT	PAINT	PAINT	PAINT
14.3 Transport hazard class(es)	3 	3 	3 	3 
14.4 Packing group	III	III	III	III
14.5 Environmental hazards	No.	No.	No.	No.

SECTION 14: Transport information**Additional information ADR**

Viscous liquid exception This class 3 viscous liquid is not subject to regulation in packagings up to 450 L according to 2.2.3.1.5.1.

Limited quantity	: 5L
Transport Category	: 3
Hazard identification number	: 30
Classification code	: F1
ADR Label Model Number	: 3
Excepted Quantity	: E1
Tunnel code	: (D/E)
Packing instructions	: P001, IBC03, LP01, R001
Mixed Packing Provisions	: MP19
Special Packing Provisions	: PP1
Special provisions	: 163, 367, 650

Additional information ADN

Viscous liquid exception This class 3 viscous liquid is not subject to regulation in packagings up to 450 L according to 2.2.3.1.5.1.

Limited quantity	: 5L
Classification code	: F1
Special provisions	: 163, 367, 650

Additional information IMDG

Viscous liquid exception This class 3 viscous liquid is not subject to regulation in packagings up to 450 L according to 2.3.2.5.

Limited quantity	: 5L
Emergency schedules	: F-E, <u>S-E</u>
Special provisions	: 163, 223, 367, 955

Additional information IATA

Passenger and Cargo Aircraft	: Quantity limitation 60L Packaging instruction 355
Cargo aircraft	: Quantity limitation 220L Packaging instruction 366
Limited Quantities - Passenger Aircraft	: Quantity limitation 10L Packaging instruction Y344
Special provisions	: A3, A72, A192

14.6 Special precautions for user : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Maritime transport in bulk according to IMO instruments : Not available.

SECTION 15: Regulatory information**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture****UK (GB)/REACH****Annex XIV - List of substances subject to authorisation****Annex XIV**

None of the components are listed above the relevant limit.

Substances of very high concern

None of the components are listed above the relevant limit.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Product/ingredient name	%	Designation [Usage]
7300 CombiColor Original Wrought Iron	≥90	3

Labelling : Not applicable.

Synthetic polymer microparticles - Designation 78

Generic identity of polymer(s) : Not applicable.

Total percentage of synthetic polymer microparticles : Not applicable.

Other EU regulations

VOC : The provisions of Directive 2004/42/EC on VOC apply to this product. Refer to the product label and/or technical data sheet for further information.

VOC for Ready-for-Use Mixture : IIA/i. One-pack performance coatings. EU limit value for this product : 500g/l (2010.) This product contains a maximum of 495 g/l VOC.

Industrial emissions (integrated pollution prevention and control) - Air : Not listed

Industrial emissions (integrated pollution prevention and control) - Water : Not listed

Ozone depleting substances

Not listed.

Prior Informed Consent (PIC)

Not listed.

Persistent Organic Pollutants

Not listed.

Seveso Directive

This product is controlled under the Seveso Directive.


Danger criteria

Category
P5c

National regulations

Product/ingredient name	List name	Name on list	Classification	Notes
neodecanoic acid, cobalt salt	EH40/2005 WELs	cobalt and cobalt compounds	Carc	-

SECTION 15: Regulatory information**EU regulations**

Industrial emissions (integrated pollution prevention and control) - Air :  Not listed

Industrial emissions (integrated pollution prevention and control) - Water :  Not listed

International regulations**Chemical Weapon Convention List Schedules I, II & III Chemicals**

Not listed.

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

CN code : 3208 10 90 00

Inventory list

Australia : Not determined.

Canada : Not determined.

China : At least one component is not listed.

Eurasian Economic Union : **Russian Federation inventory**: Not determined.

Japan : **Japan inventory (CSCL)**: At least one component is not listed.
Japan inventory (ISHL): At least one component is not listed.

New Zealand : At least one component is not listed.

Philippines : Not determined.

Republic of Korea : At least one component is not listed.

Taiwan : Not determined.

Thailand : Not determined.

Turkey : Not determined.

United States : Not determined.

Viet Nam : Not determined.

15.2 Chemical safety assessment : This product contains substances for which Chemical Safety Assessments are still required.

SECTION 16: Other information

 Indicates information that has changed from previously issued version.

Abbreviations and acronyms :

- ATE = Acute Toxicity Estimate
- GB CLP = UK CLP (EC No 1272/2008) on the Classification, Labelling and Packaging of Substances and Mixtures as amended by (EU Exit) Regulations 2019 No. 720 and amendments
- DMEL = Derived Minimal Effect Level
- DNEL = Derived No Effect Level
- EUH statement = GB CLP-specific Hazard statement
- N/A = Not available
- PBT = Persistent, Bioaccumulative and Toxic
- PNEC = Predicted No Effect Concentration
- RRN = REACH Registration Number

SECTION 16: Other information

SGG = Segregation Group
vPvB = Very Persistent and Very Bioaccumulative

Procedure used to derive the classification

Classification	Justification
Flam. Liq. 3, H226 STOT SE 3, H336 Aquatic Chronic 3, H412	On basis of test data Calculation method Calculation method

Full text of abbreviated H statements

H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H372	Causes damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

Full text of classifications

Acute Tox. 4	ACUTE TOXICITY - Category 4
Aquatic Acute 1	SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1
Aquatic Chronic 1	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1
Aquatic Chronic 3	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3
Asp. Tox. 1	ASPIRATION HAZARD - Category 1
Eye Dam. 1	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1
Flam. Liq. 3	FLAMMABLE LIQUIDS - Category 3
Resp. Sens. 1	RESPIRATORY SENSITISATION - Category 1
Skin Irrit. 2	SKIN CORROSION/IRRITATION - Category 2
Skin Sens. 1	SKIN SENSITISATION - Category 1
STOT RE 1	SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 1
STOT SE 3	SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 3

Date of printing : 12/05/2026

Date of issue/ Date of revision : 12/05/2026

Date of previous issue : 9/12/2025

Version : 11

Notice to reader

IMPORTANT NOTE: The information in this Safety Data Sheet is based on the present state of knowledge and current legislation. It provides guidance on health, safety and environmental aspects of the product and should not be construed as any guarantee of technical performance or suitability for particular applications. The information contained in this data sheet (as may be amended from time to time) is not intended to be exhaustive and is presented in good faith and believed to be correct as of the date on which it is prepared. It is the user's responsibility to verify that this data sheet is current prior to using the product to which it relates. Persons using the information must make their own determinations as to the suitability of the relevant product for their purposes prior to use. Where those purposes are other than as specifically recommended in this safety data sheet, then the user uses the product at their own risk.

MANUFACTURER'S DISCLAIMER: the conditions, methods and factors affecting the handling, storage, application, use and disposal of the product are not under the control and knowledge of the manufacturer. Therefore the manufacturer does not assume responsibility for any adverse events which may occur in the handling, storage, application, use, misuse or disposal of the product and, so far as permitted by applicable law, the manufacturer expressly disclaims liability for any and all loss, damages and/or expenses arising out of or in any way connected to the storage, handling, use or disposal of the product. Safe handling, storage, use and disposal are the responsibility of the users. Users must comply with all applicable health and safety

7300 CombiColor Original Wrought Iron

SECTION 16: Other information

laws.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.