



SAFETY DATA SHEET

Noxyde Plus

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : Noxyde Plus
Product description : Paint
Product type : Liquid.
UFI : DRQ1-Y0MJ-5005-WYV7

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses	
Consumer Industrial Professional	
Uses advised against	Reason
None identified.	-

1.3 Details of the supplier of the safety data sheet

RUST-OLEUM EUROPE
Martin Mathys NV, Kolenbergstraat 23, B-3545 Zelem, Belgium
Telephone no.: +32 (0) 13 460 200
Fax no.: +32 (0) 13 460 201

Tor Coatings Limited
Unit 21, White Rose Way, Follingsby Park, Gateshead, Tyne & Wear, NE10 8YX United Kingdom
Telephone no.: +44 (0) 191 4106611
Fax no.: +44 (0) 191 4920125
enquiries@tor-coatings.com

e-mail address of person responsible for this SDS : rpmeurohas@rustoleum.eu

1.4 Emergency telephone number

National advisory body/Poison Centre

Supplier

Telephone number United Kingdom: : +44 870 8200418 / +44 2038073798
Great Britain
Hours of operation : 24 / 7

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to UK CLP/GHS

Not classified.

The product is not classified as hazardous according to UK CLP Regulation SI 2019/720 as amended.
See Section 11 for more detailed information on health effects and symptoms.

Noxyde Plus

SECTION 2: Hazards identification**2.2 Label elements****Signal word** : No signal word.**Hazard statements** : No known significant effects or critical hazards.**Precautionary statements****General** : P103 - Read carefully and follow all instructions.
P102 - Keep out of reach of children.
P101 - If medical advice is needed, have product container or label at hand.**Prevention** : Not applicable.**Response** : Not applicable.**Storage** : Not applicable.**Disposal** : P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.**Supplemental label elements** : EUH208 - Contains (benzothiazol-2-ylthio)succinic acid, 3-aminopropyltriethoxysilane, 1,2-benzisothiazol-3(2H)-one and reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1). May produce an allergic reaction.
EUH210 - Safety data sheet available on request.
EUH211 - Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.**Supplemental label elements : Detergents - Regulation (EC) No 907/2006** : Not applicable.**Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles** : Not applicable.**Special packaging requirements****Containers to be fitted with child-resistant fastenings** : Not applicable.**Tactile warning of danger** : Not applicable.**2.3 Other hazards****Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII** : This mixture does not contain any substances that are assessed to be a PBT or a vPvB.**Other hazards which do not result in classification** : None known.**SECTION 3: Composition/information on ingredients****3.2 Mixtures** : Mixture

Product/ingredient name	Identifiers	%	Classification	Type
3-butoxypropan-2-ol	REACH #: 01-2119475527-28 EC: 225-878-4 CAS: 5131-66-8 Index: 603-052-00-8	≤3	Skin Irrit. 2, H315 Eye Irrit. 2, H319	[1]
(benzothiazol-2-ylthio)succinic acid	EC: 401-450-4 CAS: 95154-01-1 Index: 607-179-00-X	≤0,3	Skin Sens. 1, H317	[1]
3-aminopropyltriethoxysilane	REACH #: 01-2119480479-24	≤0,3	Acute Tox. 4, H302 Skin Corr. 1B, H314	[1]

Date of issue/Date of revision

: 12/03/2025

Date of previous issue

: 28/11/2023

Version : 4

2/17

Noxyde Plus

SECTION 3: Composition/information on ingredients

1,2-benzisothiazol-3(2H)-one	EC: 213-048-4 CAS: 919-30-2 Index: 612-108-00-0 REACH #: 01-2120761540-60 EC: 220-120-9 CAS: 2634-33-5 Index: 613-088-00-6	<0,036	Eye Dam. 1, H318 Skin Sens. 1, H317 Acute Tox. 4, H302 Acute Tox. 2, H330 Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 (M=1) Aquatic Chronic 1, H410 (M=1)	[1]
reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)	REACH #: 01-2120764691-48 CAS: 55965-84-9 Index: 613-167-00-5	<0,001	Acute Tox. 3, H301 Acute Tox. 2, H310 Acute Tox. 2, H330 Skin Corr. 1C, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 (M=100) Aquatic Chronic 1, H410 (M=100) EUH071 See Section 16 for the full text of the H statements declared above.	[1]

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Type

[1] Substance classified with a health or environmental hazard

This mixture contains ≥ 1% of titanium dioxide. The Annex VI classification of titanium dioxide does not apply to this mixture according to Note 10.

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures

- Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Get medical attention if irritation occurs.
- Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical attention if symptoms occur.
- Skin contact** : Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur.
- Ingestion** : Wash out mouth with water. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Do not induce vomiting unless directed to do so by medical personnel. Get medical attention if symptoms occur.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training.

4.2 Most important symptoms and effects, both acute and delayed

Over-exposure signs/symptoms

- Eye contact** : No specific data.
- Inhalation** : No specific data.
- Skin contact** : No specific data.
- Ingestion** : No specific data.

Noxyde Plus

SECTION 4: First aid measures

4.3 Indication of any immediate medical attention and special treatment needed

- Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
- Specific treatments** : No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

- Suitable extinguishing media** : Use an extinguishing agent suitable for the surrounding fire.
- Unsuitable extinguishing media** : None known.

5.2 Special hazards arising from the substance or mixture

- Hazards from the substance or mixture** : In a fire or if heated, a pressure increase will occur and the container may burst.
- Hazardous combustion products** : Decomposition products may include the following materials:
 carbon dioxide
 carbon monoxide
 sulfur oxides
 phosphorus oxides
 metal oxide/oxides

5.3 Advice for firefighters

- Special protective actions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to British standard BS EN 469 will provide a basic level of protection for chemical incidents.
- Additional information** : No unusual hazard if involved in a fire.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Put on appropriate personal protective equipment.
- For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

6.2 Environmental precautions

- : Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

6.3 Methods and material for containment and cleaning up

- Small spill** : Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Noxyde Plus

SECTION 6: Accidental release measures

Large spill : Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Dispose of via a licensed waste disposal contractor. Contain and collect spillage with non-combustible, absorbent material e. g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.

6.4 Reference to other sections : See Section 1 for emergency contact information.
See Section 8 for information on appropriate personal protective equipment.
See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

Protective measures : Put on appropriate personal protective equipment (see Section 8).
Advice on general occupational hygiene : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

7.3 Specific end use(s)

Recommendations : Not available.
Industrial sector specific solutions : Not available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

No exposure limit value known.

Biological exposure indices

No exposure indices known.

Recommended monitoring procedures : Reference should be made to monitoring standards, such as the following: British Standard BS EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) British Standard BS EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) British Standard BS EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

DNELs/DMELs

Noxyde Plus

SECTION 8: Exposure controls/personal protection

Product/ingredient name	Type	Exposure	Value	Population	Effects
3-butoxypropan-2-ol	DNEL	Long term Inhalation	270,5 mg/m ³	Workers	Systemic
	DNEL	Long term Dermal	44 mg/kg	Workers	Systemic
	DNEL	Long term Inhalation	33,8 mg/m ³	General population [Consumers]	Systemic
	DNEL	Long term Dermal	16 mg/kg	General population [Consumers]	Systemic
	DNEL	Long term Oral	8,75 mg/kg	General population [Consumers]	Systemic
	DNEL	Long term Oral	12,5 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	22 mg/kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	43 mg/m ³	General population	Systemic
	DMEL	Long term Dermal	52 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	147 mg/m ³	Workers	Systemic
3-aminopropyltriethoxysilane	DNEL	Short term Dermal	8,3 mg/kg bw/day	Workers	Systemic
	DNEL	Short term Inhalation	59 mg/m ³	Workers	Systemic
	DNEL	Long term Dermal	8,3 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	59 mg/m ³	Workers	Systemic
	DNEL	Short term Oral	5 mg/kg bw/day	General population [Consumers]	Systemic
	DNEL	Short term Dermal	5 mg/kg bw/day	General population [Consumers]	Systemic
	DNEL	Short term Inhalation	17,4 mg/m ³	General population [Consumers]	Systemic
	DNEL	Long term Oral	5 mg/kg bw/day	General population [Consumers]	Systemic
	DNEL	Long term Dermal	5 mg/kg bw/day	General population [Consumers]	Systemic
	DNEL	Long term Inhalation	17 mg/m ³	General population [Consumers]	Systemic
1,2-benzisothiazol-3(2H)-one	DNEL	Long term Inhalation	6,81 mg/m ³	Workers	Systemic
	DNEL	Long term Inhalation	1,2 mg/m ³	General population	Systemic
	DNEL	Long term Dermal	0,966 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Dermal	0,345 mg/kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	0,02 mg/m ³	Workers	Local
reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)	DNEL	Short term	0,04 mg/m ³	Workers	Local

Noxyde Plus

SECTION 8: Exposure controls/personal protection

	DNEL	Inhalation Long term	0,02 mg/m ³	General population	Local
	DNEL	Inhalation Short term	0,04 mg/m ³	General population	Local
	DNEL	Inhalation Long term Oral	0,09 mg/ kg bw/day	General population	Systemic
	DNEL	Short term Oral	0,11 mg/ kg bw/day	General population	Systemic

PNECs

Product/ingredient name	Compartment Detail	Value	Method Detail
3-butoxypropan-2-ol	Fresh water	0,525 mg/l	-
	Marine water	0,0525 mg/l	-
	Fresh water sediment	2,36 mg/kg	-
	Marine water sediment	0,236 mg/kg	-
	Soil	0,16 mg/kg	-
	Sewage Treatment Plant	10 mg/l	-
3-aminopropyltriethoxysilane	Fresh water	0,33 mg/l	-
	Marine	0,033 mg/l	-
	Sewage Treatment Plant	3,3 mg/l	-
	Fresh water sediment	0,26 mg/l	-
1,2-benzisothiazol-3(2H)-one	Soil	0,04 mg/l	-
	Fresh water	0,00403 mg/l	-
	Marine water	0,000403 mg/l	-
	Sewage Treatment Plant	1,03 mg/l	-
	Fresh water sediment	0,0499 mg/kg dwt	-
reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)	Marine water sediment	0,00499 mg/kg dwt	-
	Soil	3 mg/kg dwt	-
	Fresh water	3,39 ng/l	-
	Sewage Treatment Plant	0,23 mg/l	-
	Marine water	3,39 ng/l	-
	Soil	0,01 mg/kg dwt	-
	Fresh water sediment	0,027 mg/kg dwt	-
	Marine water sediment	0,027 mg/kg dwt	-
	Fresh water	0,00339 mg/l	-
	Marine water	0,00339 mg/l	-
Sewage Treatment Plant	0,23 mg/l	-	
Fresh water sediment	0,027 mg/kg	-	
Marine water sediment	0,027 mg/kg	-	
Soil	0,01 mg/kg	-	

8.2 Exposure controls

Appropriate engineering controls : Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

Individual protection measures

Hygiene measures : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

SECTION 8: Exposure controls/personal protection

Eye/face protection : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. Use eye protection according to EN 166. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.

Skin protection

There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals.

The breakthrough time must be greater than the end use time of the product.

The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.

Gloves should be replaced regularly and if there is any sign of damage to the glove material.

Always ensure that gloves are free from defects and that they are stored and used correctly.

The performance or effectiveness of the glove may be reduced by physical/chemical damage and poor maintenance.

Barrier creams may help to protect the exposed areas of the skin but should not be applied once exposure has occurred.

Hand protection : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. > 8 hours (breakthrough time): nitrile rubber (0.5mm)

The recommendation for the type or types of glove to use when handling this product is based on information from the following source: EN374. The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.

Body protection : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Recommended: (EN 467) Wear overalls or long sleeved shirt.

Other skin protection : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use. Recommended: organic vapour filter (Type A) particulate filter (EN 140)

Environmental exposure controls : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

Physical state	: Liquid.
Colour	: Various
Odour	: Ammoniacal. [Slight]
Odour threshold	: Not available.
Melting point/freezing point	: 0°C [Literature]
Initial boiling point and boiling range	: >100°C (>212°F) [Literature]
Flammability (solid, gas)	: Non-flammable in the presence of the following materials or conditions: open flames, sparks and static discharge, heat and shocks and mechanical impacts. Non-flammable but will burn on prolonged exposure to flame or high temperature.

Noxyde Plus

SECTION 9: Physical and chemical properties

Lower and upper explosion limit	: Not available.
Flash point	: Closed cup: >100°C (>212°F) [Literature]
Auto-ignition temperature	: Not relevant due to nature of the product.
Decomposition temperature	: Not available.
pH	: 8,3 [Conc. (% w/w): 100%] [OECD 122]
pH : Justification	: Not available.
Viscosity	: Dynamic (room temperature): 9200 to 10000 mPa·s [ISO EN BS DIN 3219] Kinematic (room temperature): 7132 to 8130 mm ² /s [calculated.] Kinematic (40°C): >20,5 mm ² /s [calculated.]
Solubility(ies)	:

Media	Result
cold water	Soluble
hot water	Soluble
methanol	Very slightly soluble
acetone	Very slightly soluble

Solubility in water	: Not available.
Partition coefficient: n-octanol/ water	: Not applicable.
Vapour pressure	: 2,3 kPa (17,25 mm Hg) [Literature]
Evaporation rate	: <1 (butyl acetate = 1)
Relative density	: Not available.
Density	: 1,23 to 1,29 g/cm ³ [20°C (68°F)] [DIN 53217]
Vapour density	: >1 [Air = 1]
Explosive properties	: Non-explosive in the presence of the following materials or conditions: open flames, sparks and static discharge and heat. No unusual hazard if involved in a fire.
Oxidising properties	: Not available.
Particle characteristics	
Median particle size	: Not applicable.

SECTION 10: Stability and reactivity

10.1 Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	: The product is stable.
10.3 Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
10.4 Conditions to avoid	: No specific data.
10.5 Incompatible materials	: No specific data.
10.6 Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Noxyde Plus

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
3-butoxypropan-2-ol	LD50 Dermal	Rabbit	3100 mg/kg	-
	LC50 Inhalation Vapour	Rat - Female	>7350 mg/m ³	4 hours
3-aminopropyltriethoxysilane	LD50 Dermal	Rabbit	4,29 g/kg	-
	LD50 Dermal	Rabbit	4076 mg/kg	-
1,2-benzisothiazol-3(2H)-one	LD50 Oral	Rat - Male	2,83 g/kg	-
	LD50 Oral	Rat - Female	1490 mg/kg	-
reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)	LC50 Inhalation Dusts and mists	Rat	0,11 mg/l	4 hours
	LC50 Inhalation Dusts and mists	Rat - Male, Female	0,5 mg/l	4 hours
	LD50 Oral	Rat - Male	490 mg/kg	-
	LC50 Inhalation Dusts and mists	Rat - Male, Female	0,171 mg/l	4 hours
	LD50 Dermal	Rabbit	92,4 mg/kg	-
	LD50 Oral	Rat	64 mg/kg	-

Conclusion/Summary : Based on available data, the classification criteria are not met.

Acute toxicity estimates

Product/ingredient name	Oral (mg/kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapours) (mg/l)	Inhalation (dusts and mists) (mg/l)
Noxyde Plus	N/A	N/A	1640024,1	6096,4	N/A
3-butoxypropan-2-ol	N/A	3100	N/A	N/A	N/A
3-aminopropyltriethoxysilane	500	N/A	N/A	N/A	N/A
1,2-benzisothiazol-3(2H)-one	450	N/A	N/A	N/A	0,21
reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)	64	92,4	N/A	N/A	0,171

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)	Eyes - Severe irritant	Rabbit	-	-	-
	Skin - Severe irritant	Human	-	0.01 Percent	-
	Skin - Severe irritant	Rabbit	-	-	1 to 4 hours

Skin : Based on available data, the classification criteria are not met.

Eyes : Based on available data, the classification criteria are not met.

Respiratory : Based on available data, the classification criteria are not met.

Respiratory or skin sensitization

Noxyde Plus

SECTION 11: Toxicological information

Product/ingredient name	Route of exposure	Species	Result
3-aminopropyltriethoxysilane 1,2-benzisothiazol-3(2H)-one reaction mass of: 5-chloro- 2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)	skin skin skin	Guinea pig Guinea pig Guinea pig	Sensitising Sensitising Sensitising

Skin : Based on available data, the classification criteria are not met.

Respiratory : Based on available data, the classification criteria are not met.

Mutagenicity

Conclusion/Summary : Based on available data, the classification criteria are not met.

Carcinogenicity

Conclusion/Summary : Based on available data, the classification criteria are not met.

Reproductive toxicity

Conclusion/Summary : Based on available data, the classification criteria are not met.

Teratogenicity

Conclusion/Summary : Based on available data, the classification criteria are not met.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Not available.

Information on likely routes of exposure : Routes of entry anticipated: Oral, Inhalation, Eyes.
Routes of entry not anticipated: Dermal.

Potential acute health effects

Eye contact : No known significant effects or critical hazards.

Inhalation : No known significant effects or critical hazards.

Skin contact : No known significant effects or critical hazards.

Ingestion : No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact : No specific data.

Inhalation : No specific data.

Skin contact : No specific data.

Ingestion : No specific data.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Short term exposure

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Long term exposure

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Potential chronic health effects

Noxyde Plus

SECTION 11: Toxicological information

Not available.

- Conclusion/Summary** : Based on available data, the classification criteria are not met.
General : No known significant effects or critical hazards.
Carcinogenicity : No known significant effects or critical hazards.
Mutagenicity : No known significant effects or critical hazards.
Reproductive toxicity : No known significant effects or critical hazards.

Other information : Not available.

SECTION 12: Ecological information

12.1 Toxicity

Product/ingredient name	Result	Species	Exposure
3-butoxypropan-2-ol	Acute EC50 >1000 mg/l Acute LC50 560 to 1000 mg/l	Daphnia spec. Fish - Guppy (<i>Poecilia reticulata</i>)	96 hours 96 hours
1,2-benzisothiazol-3(2H)-one reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)	Acute EC50 0,11 mg/l Acute EC50 0,067 mg/l	Algae - Algae Algae - <i>Pseudokirchneriella subcapitata</i>	72 hours 72 hours
	Acute EC50 0,9893 mg/l Marine water Acute EC50 2,94 mg/l Fresh water Acute LC50 2,18 mg/l Fresh water	Crustaceans - <i>Opossum Shrimp</i> Daphnia spec. - Daphnia spec. Fish - Rainbow trout	96 hours 48 hours 96 hours
	Acute LC50 8 to 13 mg/l Acute LC50 1,6 to 2,8 ppm Fresh water	Fish - <i>Alburnus alburnus</i> Fish - Rainbow trout, donaldson trout - <i>Oncorhynchus mykiss</i>	96 hours 96 hours
	Chronic NOEC 90 mg/l	Aquatic plants - <i>Phaseolus vulgaris</i>	20 days
	Chronic NOEC 1,2 mg/l Chronic NOEC 0,21 mg/l	Daphnia spec. - Daphnia spec. Fish - Rainbow trout (<i>oncorhynchus mykiss</i>)	21 days 28 days
	Chronic NOEL 0,0403 mg/l Acute EC50 0,037 mg/l Fresh water	Algae - Algae Algae	72 hours 48 hours
	Acute EC50 0,16 mg/l Fresh water Acute LC50 0,19 mg/l Fresh water	Daphnia spec. Fish - Rainbow trout (<i>oncorhynchus mykiss</i>)	48 hours 96 hours
	Acute NOEC 0,004 mg/l Marine water Chronic NOEC 0,18 mg/l Chronic NOEC 0,02 mg/l Fresh water	Algae Daphnia spec. - Daphnia spec. Fish - Rainbow trout (<i>oncorhynchus mykiss</i>)	48 hours 21 days 38 days

Conclusion/Summary : Based on available data, the classification criteria are not met.

12.2 Persistence and degradability

Product/ingredient name	Test	Result	Dose	Inoculum
3-aminopropyltriethoxysilane	EU 79/831 - C. 4-A	67 % - 28 days	-	-
1,2-benzisothiazol-3(2H)-one reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)	OECD 303A	>90 % - Readily - 1 days	-	-
	OECD 301D	>60 % - Readily - 28 days	-	-
	-	<50 % - 10 days	-	-

Noxyde Plus

SECTION 12: Ecological information**Conclusion/Summary** : This product has not been tested for biodegradation.

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
3-aminopropyltriethoxysilane 1,2-benzisothiazol-3(2H)-one reaction mass of: 5-chloro- 2-methyl-4-isothiazolin- 3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol- 3-one [EC no. 220-239-6] (3: 1)	- - -	- - -	Inherent Readily Inherent

12.3 Bioaccumulative potential

Product/ingredient name	LogP _{ow}	BCF	Potential
3-butoxypropan-2-ol (benzothiazol-2-ylthio) succinic acid	1,2 -2,93	- -	Low Low
3-aminopropyltriethoxysilane 1,2-benzisothiazol-3(2H)-one reaction mass of: 5-chloro- 2-methyl-4-isothiazolin- 3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol- 3-one [EC no. 220-239-6] (3: 1)	1,7 0,64 -0.83 to 0.75	3,4 - -	Low Low Low

12.4 Mobility in soil**Soil/water partition coefficient (K_{oc})** : Not available.**Mobility** : Nonvolatile liquid.**12.5 Results of PBT and vPvB assessment**

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Other adverse effects : No known significant effects or critical hazards.**SECTION 13: Disposal considerations**

The information in this section contains generic advice and guidance.

13.1 Waste treatment methods**Product****Methods of disposal** : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.**Hazardous waste** : Within the present knowledge of the supplier, this product is not regarded as hazardous waste, as defined by EU Directive 2008/98/EC.**Waste catalogue**

Waste code	Waste designation
08 01 12	waste paint and varnish other than those mentioned in 08 01 11

Noxyde Plus

SECTION 13: Disposal considerations

Special precautions : This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

	ADR/RID	ADN	IMDG	IATA
14.1 UN number or ID number	Not regulated.	Not regulated.	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	-	-	-
14.3 Transport hazard class(es)	-	-	-	-
14.4 Packing group	-	-	-	-
14.5 Environmental hazards	No.	No.	No.	No.

14.6 Special precautions for user : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Transport in bulk according to IMO instruments : Not available.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
UK (GB)/REACH

[Annex XIV - List of substances subject to authorisation](#)

[Annex XIV](#)

None of the components are listed above the relevant limit.

[Substances of very high concern](#)

None of the components are listed above the relevant limit.

[Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles](#)

No listed substance

[Other EU regulations](#)

VOC : The provisions of Directive 2004/42/EC on VOC apply to this product. Refer to the product label and/or technical data sheet for further information.

VOC for Ready-for-Use Mixture : IIA/i. One-pack performance coatings. EU limit value for this product : 140g/l (2010.) This product contains a maximum of 27 g/l VOC.

Industrial emissions (integrated pollution prevention and control) - Air : Not listed

Noxyde Plus

SECTION 15: Regulatory information

Industrial emissions (integrated pollution prevention and control) - Water : Not listed

Ozone depleting substances

Not listed.

Prior Informed Consent (PIC)

Not listed.

Persistent Organic Pollutants

Not listed.

Seveso Directive

This product is not controlled under the Seveso Directive.

EU regulations

Industrial emissions (integrated pollution prevention and control) - Air : Not listed

Industrial emissions (integrated pollution prevention and control) - Water : Not listed

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

CN code : 3209 10 00 00

Inventory list

Australia	: All components are listed or exempted.
Canada	: At least one component is not listed.
China	: At least one component is not listed.
Eurasian Economic Union	: Russian Federation inventory : Not determined.
Japan	: Japan inventory (CSCL) : At least one component is not listed. Japan inventory (ISHL) : At least one component is not listed.
New Zealand	: All components are listed or exempted.
Philippines	: At least one component is not listed.
Republic of Korea	: At least one component is not listed.
Taiwan	: At least one component is not listed.
Thailand	: At least one component is not listed.
Turkey	: Not determined.
United States	: Not determined.
Viet Nam	: Not determined.

Noxyde Plus

SECTION 15: Regulatory information

15.2 Chemical safety assessment : This product contains substances for which Chemical Safety Assessments are still required.

SECTION 16: Other information

✔ Indicates information that has changed from previously issued version.

Abbreviations and acronyms :

- ATE = Acute Toxicity Estimate
- GB CLP = UK CLP (EC No 1272/2008) on the Classification, Labelling and Packaging of Substances and Mixtures as amended by (EU Exit) Regulations 2019 No. 720 and amendments
- DMEL = Derived Minimal Effect Level
- DNEL = Derived No Effect Level
- EUH statement = GB CLP-specific Hazard statement
- N/A = Not available
- PBT = Persistent, Bioaccumulative and Toxic
- PNEC = Predicted No Effect Concentration
- RRN = REACH Registration Number
- SGG = Segregation Group
- vPvB = Very Persistent and Very Bioaccumulative

Procedure used to derive the classification

Not classified.

Full text of abbreviated H statements

H301	Toxic if swallowed.
H302	Harmful if swallowed.
H310	Fatal in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
EUH071	Corrosive to the respiratory tract.

Full text of classifications

Acute Tox. 2	ACUTE TOXICITY - Category 2
Acute Tox. 3	ACUTE TOXICITY - Category 3
Acute Tox. 4	ACUTE TOXICITY - Category 4
Aquatic Acute 1	SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1
Aquatic Chronic 1	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1
Eye Dam. 1	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1
Eye Irrit. 2	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2
Skin Corr. 1B	SKIN CORROSION/IRRITATION - Category 1B
Skin Corr. 1C	SKIN CORROSION/IRRITATION - Category 1C
Skin Irrit. 2	SKIN CORROSION/IRRITATION - Category 2
Skin Sens. 1	SKIN SENSITISATION - Category 1
Skin Sens. 1A	SKIN SENSITISATION - Category 1A

Date of printing : 12/03/2025

Date of issue/ Date of revision : 12/03/2025

Date of previous issue : 28/11/2023

Version : 4

Notice to reader

Noxyde Plus

SECTION 16: Other information

IMPORTANT NOTE: The information in this Safety Data Sheet is based on the present state of knowledge and current legislation. It provides guidance on health, safety and environmental aspects of the product and should not be construed as any guarantee of technical performance or suitability for particular applications. The information contained in this data sheet (as may be amended from time to time) is not intended to be exhaustive and is presented in good faith and believed to be correct as of the date on which it is prepared. It is the user's responsibility to verify that this data sheet is current prior to using the product to which it relates. Persons using the information must make their own determinations as to the suitability of the relevant product for their purposes prior to use. Where those purposes are other than as specifically recommended in this safety data sheet, then the user uses the product at their own risk.

MANUFACTURER'S DISCLAIMER: the conditions, methods and factors affecting the handling, storage, application, use and disposal of the product are not under the control and knowledge of the manufacturer. Therefore the manufacturer does not assume responsibility for any adverse events which may occur in the handling, storage, application, use, misuse or disposal of the product and, so far as permitted by applicable law, the manufacturer expressly disclaims liability for any and all loss, damages and/or expenses arising out of or in any way connected to the storage, handling, use or disposal of the product. Safe handling, storage, use and disposal are the responsibility of the users. Users must comply with all applicable health and safety laws.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.